



Product Catalogue

Traffic Control Management System

Security > Corporate Solutions > Traffic Control Management System



Traffic light



KT Automation Private Limited · D 32-33 Kamalanjali Commercial Complex,
Radhakrishna Crossing, Akota · 390020 Vadodara



Ref: KT116022900TTLR

300 MM Dia Traffic Light RED

SIZE - 300MM

Color - Red

BODY -Polycarbonate ,Suitable for extreme conditions

LIGHT SOURCE- Ultra bright LEDS

LENS- UV Stabilized,Waterclear Polycarbonate

FRONT HOOD - made of HDPE

Traffic Signal Light -230V Operated



Scan product

Ref: KT116022900TTLA

300 MM Dia Traffic Light Amber

300 MM POLYCARBONATE

LED BLINKER WORKING ON 230 VOLT

,Suitable for extreme conditions LIGHT SOURCE- Ultra bright

LEDS LENS- UV Stabilized,Waterclear Polycarbonate FRONT

HOOD - made of HDPE Traffic Signal Light -230V Operated



Scan product



Ref: KT116022900TTLG

300 MM Dia Traffic Light Green

SIZE - 300MM

Color- Green

BODY -Polycarbonate ,Suitable for extreme conditions

LIGHT SOURCE- Ultra bright LEDS

LENS- UV Stabilized,Waterclear Polycarbonate

FRONT HOOD - made of HDPE

POWER SUPPLY - 230 V



Scan product

Ref: KT116022900TTRG

300 MM Dia Traffic Light 2 In 1 Red, Green 230V Operated

SIZE - 300MM

Color- Green +Red In Single Light

Arrow - Green upside

Cross - Red

BODY -Polycarbonate, Suitable for extreme conditions

LIGHT SOURCE- Ultra bright LEDS

LENS- UV Stabilized,Waterclear Polycarbonate

FRONT HOOD - made of HDPE

POWER SUPPLY - 230 V



Scan product



Ref: KT104015001INSC

Serenity CAM Speed display Board with ANPR Camera



SPEED DISPLAY Board with ANPR Camera
 SPEED DIGIT Height: 16 inches, Display: 7 Segment
 "YOUR SPEED" legend 1.37-inch, spell "YOUR SPEED"
 Customizable message
 LED's Ultra-bright, 3-row thick, tri-color: Amber, Green, Red
 LEGALITY 300+ m
 POWER CONSUMPTION Average < 150W

Pole and Pole fixing in client scope
 Cloud charges per anum per device will be extra Note:
 1. 230V Supply in ...



Scan product

Ref: KT10300600ANPSA

ANPR Camera INT21 PNPR1



ANPR Camera
 Model No.: INT21-PNPR1
 Recognition Camera : Up to 30 Meter
 Compression : H.264
 Data Protection : AES Encrytion
 Deep Learning Based AI Engine
 Trained Over 10 Millions Images
 Specially Designed for Indian Number Plates
 Resolution : 4 MP
 IR Range : 20 Meter
 Lens: 12 mm Fixed
 Frame Rate : 30 FPS



Scan product



Ref: KT103006AN041L3

ANPR Camera Model No CP-UNC-TT41L3-VMD-Q



ANPR Camera

Model no.: CP-UNC-TT41L3-VMD-Q

- 1/1.8" 4 MP CMOS sensor (1.411 centimeters)
- Max. 4MP (2688 × 1520)@30fps
- H.265, H.264M, H.264H, H.264B, MJPEG
- 10 mm-50 mm Motorized Lens
- WDR(140dB), Day/Night(ICR), 3D NR, BLC, HLC
- IR Range of 30 Mtr., IP67, IK10 System



Scan product

Ref: KT10401500TRCM2

Laser Speed Camera LTI 2020 TruCAM II



Model -LTI 20/20 TruCAM II

Handheld Day & Night Photo

Lidar with Standard accessories (TruCAM

Shoulder Stock, Trucam LCD Stylus-2 nos, Turcam

Sun Shade - 1 No, 12V Charger- 1, High capacity SD

Reader-1, 32GB Card-1, Rechargeble Battery pack-

2 Nos, Pelican hard case with foam)



Scan product



Ref: KT116022003TS20G

200 MM Dia Traffic Light

200 MM DIA (IP 65 CERTIFIED)
SIGNAL HEAD with unbreakable polycarbonate housing with
transperent lens including glass epoxy PCB with superbright
hight intensity traffic grade
LED's working on 230 VOLT /12V/24V



Scan product

Ref: KT116022900T1RG

300 MM Dia Traffic Light 2 In 1 Red, Green 12V DC Operated

SIZE - 300MM
Color- Green +Red In Single Light
Arrow - Green upside
Cross - Red
BODY -Polycarbonate, Suitable for extreme conditions
LIGHT SOURCE- Ultra bright LEDS
LENS- UV Stabilized,Waterclear Polycarbonate
FRONT HOOD - made of HDPE
POWER SUPPLY - 12V DC



Scan product



Ref: KT116022900CR30

300 MM Dia Cross Green arrow Traffic Light



SIZE - 300MM

VOLT : 12V & 24V

Color- Green Arrow +Red Cross In Light

Colours - Red - 625 nm , Green - 500 nm

BODY -Polycarbonate, Suitable for extreme conditions

Lens / Housing UV stabilized polycarbonate

Luminance Intenisty - Red - 400 cd , Green - 400 cd

Weight - Less than 2 kg

Protection - IP 65

Dimension - 310 mm X 310 mm X 100 mm

Power Consummption - Between 11 - 12...



Scan product