



Product Catalogue

Fire Safety Solutions

Safety > Fire Safety Solutions



KT Automation Private Limited · D 32-33 Kamalanjali Commercial Complex,
Radhakrishna Crossing, Akota · 390020 Vadodara



Ref: KT107001001AGMS

Manual Call Point MS Housing AD101 AC

Agni Manual Call Point

Model-AD 101 AC

MS Housing With Chain and Hammer (220VAC)

Voltage :220V AC



Scan product

Ref: KT107001001OP72

Optical Smoke Detector with Base Siemens OP720

Smoke detector consisting of:

- Point detector
- Detector dust cap to protect the point detector during the construction phase

Function:

- Functions according to the scattered light principle with one sensor, optical forward scattering
- Opto-electronic measuring chamber which obstructs disruptive extraneous light but provides excellent detection of smoke particles
- Selectable...



Scan product



Ref: KTI07003001CE22

Fire Blanket 2 X 2

Signature Fiberglass Fire Blanket

Model No.: DSZFG0.6

Working Temp.: 600 C To 900 C

Colour : White

Thickness : 0.6 MM

Size : 2 X 2 Meter



Scan product

Ref: KTI08002001SSP3

Intrusion System Atigo AlarisV2 Panel

SMART SAFETY PANEL - ALARISV2

PACKAGE DETAILS-1 Passive Infra-Red Sensor,1 Siren,1 Door Sensor,2 Remote Controllers,1 Adapter

Specification-

Remotely Operated Wireless Security Panel With English Voice Prompt.

96 Wireless and 3 Wired Defense Zones; Each Could Be Programmed Independently. Can Be Operated With 99 Remote Controls. Sensor Low Voltage Alarm & Sensor Tamper Alarm Eng...



Scan product



Ref: KT107005001FBWS

Fire Bucket Wall Stand

Fire Bucket Stand

□ Type : Single Bucket Stand

□ Material : MS

□ Color : Red

□ Features : It Can hold in single Pieces.

□ Application : Fire Fighting Operation at Initial Stage

□ Warranty:- Not Applicable



Scan product

Ref: KT107006004CLEN

Fire Extinguisher 4 kg Clean Agent Refilling

Fire Extinguisher 2 kg Clean Agent (Refilling)



Scan product



Ref: KT107005001FSWB

Canopy fire bucket stand

Canopy Fire Bucket Stand with 4 Bucket

- Type : Four Bucket Stand
- Material : MS Square Tube and 3ft X 2ft Galvenised Sheet .
- Size : Height 3.5 Ft , 3ft Wide.
- Color : Red
- Weight : 7 Kg
- Roof Protects From Dirt and Rain. Four Hooks Provided to
- Hang the Bucket . Good Powder Coated Finish. Rubber
- Grommet is Provided at Each Hole.
- Standard Packing : 01 Stand.
- Appli...



Scan product

Ref: KT107001001THMS

GSM Mobile Based Temperature and Humidity Monitoring system

A GSM Based Alert System for Humidity and Temperature Monitoring For critical Rooms Like Server room, Hub Room, Data Centre, Laboratories, Medicine storage, warehouse in remote location can be monitoring from anywhere and anytime

Latest Microcontroller Based Technology
Temperature and humidity monitoring from anywhere with Current Real time and Date.

- Big LCD Digital Display ...



Scan product



Ref: KTI07001001AG12

Fire Alarm System 12 Zone Agni

Features Of Agni Device 12 Zone Conventional Fire Alarm Panel

- Agni Device 12 Zone Conventional Fire Alarm Panel
- Complies to IS 2189:1999 & Tested by ERTL (N) & System Sensor
- 2 x 16 character Backlit LCD Display (4 x 20 Character, Optional)
- 64 / 128 / 256 Events Logging Facility With Real Time Clock & Keypad
- 2 Wire Communication facility via RS 485 Port
- BMS Attachmen...



Scan product

Ref: KTI07008002ZCG

Gas Detection System 2 Zone Conventional Gas Detection System

Model : GDS-2

2 Zone Conventional Gas Detection System (Family-Gas)
GDS-2 zone conventional gas detection System protects home as well as commercial premises

- Two-zone gas detection system is capable of monitoring gas detection devices, like as gas detectors & providing alarm.
- The detector goes into alarm condition due to gas or heat detection. Early gas detection depends o...



Scan product



Ref: KTI0700800IGLD

Gas Detection System TrueSafe Industrial Gas Leak Detector for Hydrogen



Product Description: TS21I-CAT

Model TrueSafe TS21I-CAT gas detector is used to detect natural gas, LPG, coal gas, alkane, combustible gas, and gasoline, Alcohol, ketone, benzene etc., organic solvent as well as Hydrogen gas. Application area of this detector is in Automotive, Medical, Refineries and Petrochemical Plants, Oil and Gas, LPG station, Chemical and Pharma Industr...



Scan product

Ref: KTI01001001PAXE

Fireman Axe 20,000 Volt Tested

20,000 Volt Tested Fireman Axe

Type Of Axe Fireman Axe

Material MS

Usage/Application Fire fighting

Warranty: NA



Scan product



Ref: KTI16017002HXTI

Honeywell Gasalert MAX XT II Multi Gas Detector with In Built Pump

Honeywell BW™ Solo
Serviceable Single-gas Detector

The easiest single-gas detector to service, with no need to take it apart to replace sensors, batteries and sensor filters. That means long life and low cost.

- Complete with an extensive selection of sensor options. Count on comprehensive detection, whether you're monitoring for common or exotic hazards.
- The first single-gas...



Scan product

Ref: KTI16017002HMX3

Honeywell Gasalert Microclip X3 without in built pump

Honeywell BW™ Solo

With out pump

Multigas Detector - for 4gases (H2S, O2, CO, LEL)
without in-built pump model: Gasalert Microclip X3

make: BW technologies,

Detector complete with specified sensor(s), stainless steel alligator clip and concussion-proof housing

Rechargeable battery

Wall outlet charging adaptor

Calibration/test cap and hose

Manual



Scan product



Ref: KT107001001TWL4

Tower Light 4 LED With SOUND

Tower Light With 4 LED +Sound

Voltage: 12 V Dc

Warranty:- 1 Year



Scan product

Ref: KT107001001ZDMC

Manual Call Point Bosch

FMC-210-DM Double Action Call Points

Mechanical blocking of locking mechanism after alarm triggering

Individual identification thanks to automatic or manual detector addressing

Indicator LED for alarm or for inspection Evaluation



Scan product



Ref: KT107001001ZDSO

Outdoor Siren Bosch

FNM-420-B-RD Sounder outdoor, red

Volume of up to 102.5 dB(A)

u Maximum current consumption of less than 4.05 mA

u Up to 75 sounders per LSN 0300 A loop and 100 per LSN 1500 A loop

u Immediate synchronization

u 32 different tone types can be selected (incl. DIN tone)



Scan product

Ref: KT107001002P994

P 9945A Loop Network Card GST

P-9945A Loop Network Card

Features

□ Two photoelectric isolation RS485 interfaces.

□ Suitable for ring network

P-9945A Loop Network Card



Com. Interface -Two RS485 interfaces

Com. Distance -The distance between two neighbor nodes is less than 1200m

Network Capacity Maximum 32 GST series control panels for networking

Transmission Medium 1.0 mm² or above twisted pair, shielded twisted pair is recommende...



Scan product



Ref: KT107006003DCP6

Fire Extinguisher DCP 6 Kg Refilling

Refill of Existing Fire Extinguisher
6 KG DCP



Scan product

Ref: KT107006003DCP9

Fire Extinguisher DCP 9 Kg Refilling

Refill of Existing Fire Extinguisher
9 KG DCP



Scan product



Ref: KT107006001S6DCP

Fire Extinguisher 6 kg DCP



SODIUM BICARBONATE BASE POWDER Dry chemical powders are important fire fighting agents as they are stable, free flowing and easy to handle
Extinguisher media :DRY Powder IS 4308
Discharges Time Min.: 13 Seconds



Scan product

Ref: KT107006001S9DC

KANEX DCP type Fire extinguisher cap. 9 Kg



"KANEX" DCP type Fire extinguisher cap. 9 Kg.
filled with with Mono Ammonium Phosphate
KANEX MARQ-9-40% confirm to IS 14609

- Design-Hose & Nozzle
- Fire Rating (MAP-50%) - 6A : 183B
- Height (Approx.) - 585 mm
- Diameter (Approx.) -180 ± 5 mm
- Average Discharge time-31 Sec
- Average Range of throw-6 m
- Average % Discharge-94%
- Operating Temperature--30 °C to +60 °C
- Service/Ma...



Scan product



Ref: KT107006003DCM9

Fire Extinguisher DCP Metal 6 Kg Refilling



Metal fire extinguisher Refilling
6 KG DCP (METAL)



Scan product

Ref: KT107002001FBAFO

Fire Ball AFO



Fire Extinguisher Ball
Capacity :1.25 kg
Diameter : 15 CM
Brand : AFO
Fire Class : C
Material : Non-Toxic Mono Ammonium Phosphate
Usage/Application : Factory, Shopping Mall, Gas Station,
Hotel,Car
Weight :1.3 Kg
Noise : Approximately 138 decibel(When the ball explodes)



Scan product



Ref: KTI07006001S9DCP

Fire Extinguisher 9 kg DCP

SODIUM BICARBONATE BASE POWDER Dry chemical powders are important fire fighting agents as they are stable, free flowing and easy to handle

Extinguisher media :DRY Powder IS 4308

Discharges Time Min.: 13 Seconds



Scan product

Ref: KTI07003001WJAG

Water Jel Fire Blanket Agni Kawach

Size - 5 ft x 6 ft

Usage/Application Fire Fighting

Brand : Agni Kavach

Color : Silver

Materials Woolen blanket with water soluble and biodegradable GEL.



Scan product



Ref: KTI07006001S6CL

Fire Extinguisher KANEX 6 Kg Clean Agent



KANEX KCARQ-6 CLEAN
AGENT TYPE FIRE EXTINGUISHER - 6KG
Clean Agent 6 kg Fire
Extinguisher filled with HFC
Based gas, Electrically
nonconductive noncorrosive,
colorless and non-residual gas, Applicable classes A, B, C,
and
electrical fires, UGTS PressureGauge, Gross Weight 8.9 Kg,
empty Weight 2.9 Kg, Can
Height 530mm, Diameter 150 Å ± 10mm, Discharge Time
22Sec, Controllable dis...



Scan product

Ref: KTI01001001HOSE

Flexible Fire Fighting Hose



"PREMIER" BRAND FLEXIBLE FIRE FIGHTING DELIVERY HOSE
All synthetic fiber circular woven jacketed, EPDM synthetic
REINFORCED RUBBER LINED (RRL) delivery fire hose,
Dia. 63mm X 15mtr length,
Working Pressure 14kg/cm², Proof Pressure 23kg/cm², Min.
Burst Pressure 38kg/cm²,
BEARING IS: 636-2018 TYPE 1, ISI MARK, CE MARKED,
Dully fitted with Hose Coupling made of SS 304, Pair of ma...



Scan product



Ref: KT107007002AFSU

Arc Flash Suit

Arc Rating – ATPV 40 cal/cm2

- Coat with open end zip closure and hook and loop covered with flap. ➤ One-piece topstitched, lay flat collar.
- Adjustable straps with hook and loop closures on sleeve cuffs.
- Bib overall with side elasticized waist and adjustable suspender.
- Lower half of garment has felled inseams.
- FR thread used throughout garment construction.

Test Re...



Scan product

Ref: KT10800200MSIR

Wireless Signal Repeater Visonic

Model No. RP-600 PG2

PowerG two-way Frequency Hopping Spread Spectrum FHSS-TDMA technology -provides robustness and reliability close than ever to wired

- Extends the communication range between the PowerMaster systems and other PowerG transmitters
- Transmission range is by far greater than the industry standard
- Visible link quality indication shown on the device
- Mains po...



Scan product



Ref: KT107006001S4FC

Kanex 4 Ltr F Class WET Chemical Fire SS Body Type Fire Extinguisher

K Class Kitchen Wet chemical (Blend of Potassium Acetate, Potassium citrate or Potassium carbonate) 4 Ltr. Fire Extinguisher, Smooth and Polished Stainless Steel body, Applicable fire class K, UGTS Pressure Gauge, Can Height 550 mm, Diameter 150 $\pm$ 10mm, Discharge Time 13 Sec, Jet Range 2 Meters, Average Discharge is 95%, Controllable discharge mechanism with EPDM Hose & Specia...



Scan product

Ref: KT107006001S6DC

KANEX DCP type Fire extinguisher cap. 6 Kg

"KANEX" DCP type Fire extinguisher cap. 6 Kg. filled with Mono Ammonium Phosphate Powder 50% confirm to IS 14609

- Design-Hose & Nozzle
- Fire Rating (MAP-50%) - 4A : 144B
- Height (Approx.) - 540 mm
- Diameter (Approx.) - 150 $\pm$ 5 mm
- Average Discharge time-24 Sec
- Average Range of throw-5 m
- Average % Discharge-94%
- Operating Temperature--30 $^{\circ}$ C to +60 $^{\circ}$ C
- Service/Max. service...



Scan product



Ref: KT107001001ZWSC

Zone wise Sounder card

Zone wise Sounder card



Scan product

Ref: KT107006001LI6S

KFLIHQ-6 Lithium Store Pressure Fire Extinguisher 6 kg

KANEX KFLIHQ-6 LITHIUMION STORED PRESSURE FIRE EXTINGUISHER -6 KG

Lithium Ion stored pressure Fire Extinguisher Cap. 6 ltr. filled with Water additive Aqueous Vermiculate Dispersion (AVD), UGTS Pressure Gauge, Discharge Duration- 120-130 sec, Range 2.5-3.5 m, CanHeight 530 mm, Diameter 150 Å± 10mm, Min. Discharge Time 13 Sec, Controllable discharge mechanism, applicable on Clas...



Scan product



Ref: KT107006001S4DC

Fire Extinguisher KANEX 4 kg DCP

A Dry Chemical Fire Extinguisher is the most common type used in Australia. It is also known as a DCP, BE, or ABE fire extinguisher. To determine if a fire extinguisher is a dry chemical type, one simply needs to look for the white band that runs around the tank.

Powder : sodium bicarbonate

SBC/PBC Chemical powder capable of fighting against class B,C & Electrically started fir...



Scan product

Ref: KT107006001SSDC

Fire Extinguisher 75 kg DCP

KANEX KFDRQ-75-50% ABC FIRE EXTINGUISHER CAP

Brand : Kanex



Scan product



Ref: KTI07006001W9C

Fire Extinguisher KANEX 9 kg CO2 Water Type Stored Pressure



KFWSRQ-9

KANEX 9 ltr. Water type stored pressure Fire Extinguisher filled with water of TDS 3 to 4 PPM, Applicable fire class A, UTGS Pressure Gauge, Gross Weight 12 Kg, empty weight 4.3 Kg, Can Height 575mm, Diameter 180 ± 10mm, Discharge Time 35 Sec, Controllable discharge mechanism, Jet Range 7 Meters, Average Discharge is 95%, applicable on Class A, Fire Rating- 3A, Can...



Scan product

Ref: KTI07013001MNFP

Explosion Proof Portable Emergency Light



Model : PEL LED NM / FP (HL)

CONFORMS TO : IS - 10322)

ingress protection : IP 65)

Housing Cast : Aluminium, cmri certified fame proof resistant, Clear borosil glass.)

paint & Colour :Epoxy paint, Shade 631 of IS : 5)

Diffuser : Heat resistant, clear BOROSIL GLASS diffuser)

Input (V) : ~ 230 Volts, 50 Hz; ±10%)

LED Make : Edison, Osram, Lustrus)

Recharging Cycle : 16 to 24 hour...



Scan product



Ref: KT101001001P991

ProgrammerTool GST Addressable fire Alarm sensor

Programmer Tool.
GST Addressable fire Alarm sensor



Scan product

Ref: KT101001002PAXE

Fireman Axe 50,000 Volt Tested

50,000 Volt Tested Fireman Axe
Type Of Axe Fireman Axe
Material MS
Usage/Application Fire fighting
Warranty: NA



Scan product



Ref: KT107001001AFSP

Addressable Photoelectric Smoke Detectors Notifier FSP951R

FSP/951R : heat detector Honeywell notifier WITH B-501 : base



SLC LOOP:

- Two-wire SLC loop connection:
- Unit uses base for wiring:
- Compatible with FlashScan and CLIP protocol systems:
- Stable communication technique with noise immunity:

ADDRESSING::

- Addressable by device:
- Rotary, decimal addressing:

(Refer to the NOTIFIER panel manuals for device capacity.):
Walk test...



Scan product

Ref: KT107001001MFHB

MCP Hooter Combo with Battery

Flasher MCP Hooter Combo with Battery Back up & Reset options

combo with Battery back up

Loud Sound,

Very Good Flashing,

Low Battery Indication,

System ON Indication,

Metal Body,

Reset Option, To work in AC supply failure easily

220 Volt AC

battery back up. 2-3 hours



Scan product



Ref: KTI07001001MISO

Honeywell Morley Strobe Sounder MI WSO PR N



Morley IAS MI-WSO-PR-N Wall Mounted Red Sounder
BASE :B501AP
Material : ABS
Color :Red
Operating Temperature : -25 to +70 deg C
Shape : Round
Supply Voltage: 15 to 29VDC (Non-isolation) 15 to 29VDC (Isolation)
Standby Current: 120μA (Non-Isolation) 225μA (Isolation)
Max current consumption sounder and strobe: 14.5mA (High Volume Tone 11 @15V)
Max Sound Output 99 dB(A) +/-3dB ...



Scan product

Ref: KTI07001001MWBR

Strobe With Buzzer Mini



Model : LTE-2071J
Siren type :
Strobe type : Red
Operating Voltage : 220AC
Dimensions : (L)270mm x (W)193mm x(H) 100mm
Recommended Battery : 12VDC, 1.3Ah rechargeable
Colour : White
Stand by Current : 8mA
Maximum Current : 1600mA@13.8VDC
Maximum Power : 1500(Peak)
Charge Current Limit : 250mA
Low Battery Level : 8VDC,+0.3VDC
Warranty:- 1 Year



Scan product



Ref: KTI07001001R258

8 Zone Fire Alarm Control Panel Model 2558

Model : RE-2558

Make : Ravel

Supply of 8 zone fire alarm control panel ,with 16x2 character LCD Display

Complies with UL-864 AND NFPA-72, Standard .

Type :Conventional

Dimensions : (440W X 340H X 120D)

Color : Red / White

Construction : 18 Gauge (1.22mm) CRCA sheet with powder-coated Finish

IP Rating : IP50

Cable Entry : 11xø19mm Knockout in top of the cabinet
10xø22.25mm ...



Scan product

Ref: KTI07001001THSS

GSM Mobile Based Temperature and Humidity Monitoring system with Display

A GSM Based Alert System for Humidity and Temperature Monitoring System with Display

Display: Character size: 2.3 Inch

Alert with big display for Temp and Humidity data with RS 485 approx 100 meters

For critical Rooms Like Server room, Hub Room, Data Centre, Laboratories, Medicine storage, warehouse in remote location can be monitoring from anywhere and anytime

Latest Micro...



Scan product



Ref: KT107001001TLMP

LM PRO Temperature Humidity Data Logger with Display



LM_Pro ; Temperature & Rh Data Logger with Display
Communication : Direct USB

Sensor : Internal

CODE 4110-40

No of Data :100,000 (50,000 for Temperature & 50,000 for Rh)

Logging Interval User programmable from 5 Sec to 18 hours via software

Resolution 0.01 °C - Display and storage

Software: LMView software (Without 21CFR compliant).



Scan product

Ref: KT107001001TLMT

LM TRANSIT Single Use Temperature Data Logger Without Display



Single Use Temperature Data Logger Without Display

Communication : Direct USB

Sensor : Internal

CODE 4000-23

No. of Data : 16,000

Store Interval : 15 Min. (Approximately 150 Days)

Easy to Use

Indication for start of logging

Cost Effective, single use data logger

Built-in memory to record upto 4000/8000/16000/32000 data records Storage resolution 0.Q1

EN12830 Compliant

'Direct c...



Scan product



Ref: KT107001002THMS

IOT Mobile App Based Temperature and Humidity Data logger

IOT/Mobile app based Temperature and Humidity Data Logger with Alerts

Email notifications free for 1 year

After 1 year Cloud charges will be extra



Scan product

Ref: KT107001002TWLF

Electronic Hooter with Flasher

Sound Level (dB) 110db

Power Source 24,110,230 VAC,DC

Alarm Range 100 met

Usage Electrical control panel,Electrical Switch gear,Safety

Brand MIMIC

Supply Voltage :- 18 vdc min. to 30 vdc,110v AC,230v ac

Sound level :- 105dB

Environmental rating :- IP50

Maximum input response time On/Off :- 10 ms

Oscillation Frequency :- 3kHz + 500 Hz LED or audible independently selected(option...



Scan product



Ref: KTI07003001FB56

Water Jel Fire Blanket Pouch 5'x6'

Case Pack: 4 pouches individually boxed

Case Weight: 56 lbs.

Case Size: 19.5in. x 11.75in. x 11in. (49.5 x 29.9 x 27.9 cm)

Blanket Dimensions / Unit: 6' x 5' (182.8 x 152.4 cm)

A full-size blanket that adequately covers a burn patient and can be used to extinguish flames and smoldering clothes or dangerous white phosphorous. Conveniently packaged in a flat, durable foil pouch t...



Scan product

Ref: KTI0700300HSC3

Signature Welding Blanket Size 2 X 2 Meter

Signature Welding Blanket

Model No. : KTZVCF3.2

Temp. : 1260 C to 1760 C

Size : 2 x 2 Meter

Colour : Brown (SS Metallic Reinforced) OR Vermiculite Coated Ceramic.



Application: This Cloth Is Widely Used In Welding, Foundry Works, Aluminum And Steel Mills, Boiler Insulation And Seal, Shipyards, Refineries, Power Plants And Chemical Plants.



Scan product



Ref: KT107006001S9FC

Kanex 9 Ltr. F Class WET Chemical Stored Pressure SS Body Type Fire Extinguisher

Kanex 9 Ltr. F- Class WET Chemical Stored Pressure SS Body Type Fire Extinguisher

- Capacity-9 Ltr
- Design-Hose & Nozzle
- Fire Rating- 8A : 40F*
- Height (Approx.)-610 mm
- Diameter (Approx.)-180 ± 5 mm
- Average Discharge time-30 Sec. •Average % Discharge-95%
- Operating Temperature-+5 °C to +55 °C
- Service/Max. service/Test Pressure-9 / 15 / 35 bar
- Expelling Agent-Nitrogen (UHP ...



Scan product



Ref: KT107006001S9KT

Fire Extinguisher KANEX 9 kg K Class Kitchen Wet chemical

KFKHQ-9

"KANEX" 9 Ltr. Fire Extinguisher K Class Kitchen Wet chemical (Blend of Potassium Acetate, Potassium citrate or Potassium carbonate), Smooth and Polished Stainless Steel body, Applicable fire class K, UGTS Pressure Gauge, Can Height 620 mm, Diameter 180 ± 10mm, Discharge Time 13 Sec, Jet Range 2 Meters, Average Discharge is 90%, Controllable discharge mechanism with EPD...



Scan product



Ref: KT107006002FHYT

Hydrostatic Testing For Fire Extinguisher

Hydrostatic testing is the process of pressure testing rechargeable fire extinguisher components—shell, cylinder, hose assembly, etc.—with a liquid, such as water, in order to ensure that it has no leaks or structural flaws



Scan product

Ref: KT107007001CO2F

Co2 Flooding System

Co2 Flooding System.

Warranty:- Not Applicable



Scan product



Ref: KT107007002H8CA

HONEYWELL ARC FLASH PROTECTION COAT PANT KIT 8 CAL

Part Code: INSKCP8RB

Manufacturer: HONEYWELL

Specification

- 8 cal/cm² ATPV ratings
- Made from arc flash resistant material
- Sewn with Nomex® thread
- Meet current ASTM F1506 and NFPA 70E 2012 Standards.
- All are CE 0120 certified.
- Ki...



Scan product

Ref: KT107008002PG1D

Portable Gas Detector PG 100 D

PG-100-D (Diffusion Type)

Gas to be Detected: LPG

Range: 0-100% LEL

Sensor: Pallister Gas Sensor

The Plug-in Sensor provides a full year of warranted protection against hazardous gases

- The Portable Detector detects smallest gas leak on service line and joints
- Easy handling and programming with 3 keys and one key for power ON/OFF
- Easy software calibration by using front ke...



Scan product



Ref: KT10700800PD650

Single Gas Detection Device

Model no.:Dräger Pac 6500

•Single-Gas Detection Device

Model : Dräger

The robust Dräger Pac 6500 is your reliable companion under tough conditions.

The personal single-gas detection device measures CO, H₂S, SO₂ or O₂ quickly and precisely. Quick sensor response times and a powerful battery also ensure safety.

Strong performance for maximum safety

You can rely on the Dräger Pac...



Scan product

Ref: KT10700800TSH2

Industrial Hydrogen Gas Leak detector

MODEL NO.TS21I-CAT-H2

TrueSafe catalytic type Industrial Gas Leak detector for Hydrogen

ATEX & PESO Certified enclosure Gas Detection Method using Catalytic Combustion.

Detection Range: 0-100% of LEL.

Preset Alarm Levels : a) Low Alarm Level. b) High Alarm Level.

Auto Calibrated.

Response Time(< 2Sec.).

Catalytic sensor is used.

PFC Relay NO or NC O/P and It will be Selectable ...



Scan product



Ref: KTI07009001FD03

Hybrid Smoke and Temperature Detector tFD03



Heat + Smoke Detector
Dust-proof, Moth Proof, Anti White light Interference
Anti RF Interference
Reliable Stability
Sound and Flash Alarm/ LED Indications
Infrared Photoelectronic sensor
Hush Button
SMT Manufacture Technology
CE Certified
UL Compliant - Built as per UL Specifications
Attractive and decent appearance

Specification

Operating Voltage 9VDC
Alarm Indication LED flashes in red
Alarm Sound ≥ 85 dB / 3m
Humidity $\leq 95\%$ RH
Dimension $\Phi 128 \times 38$ mm
Detecting Area 80 m² at 6-12 m installation height
60...



Scan product

Ref: KTI07010001SDCR

CRC Smoke Detector Tester



Simulates smoke - Provides a true, functional test for commercial and residential smoke detectors
Aerosol extends user reach up to 120cm - Allows testing to be done while standing safely on the floor
Smokeless aerosol - Detectors will remain in proper working order after each test without build-up of carbon residue
Non-Staining - Will not discolour painted ceilings, walls or sm...



Scan product



Ref: KT10800200MC30

MC 302 PG2 PowerG Wireless Door, Window Contact



Battery type: 3V, CR-123 Lithium battery
temperature: 0°C to 49°C (32°F to 120°F)

Operating environment: Indoor

Dimensions: 81 x 34 x 25mm (3.19 x 1.25 x 1in)

PowerG two-way Frequency Hopping Spread Spectrum FHSS-TDMA technology - provides robustness and reliability closer than ever to wired

- Ideal for protecting doors and windows
- Large transmission range enabling repeater-fre...



Scan product

Ref: KT116017002HBWC

Honeywell BW Solo BLE Wireless Version CO Gas Detector



Honeywell BW™ Solo

Serviceable Single-gas Detector

The easiest single-gas detector to service, with no need to take it apart to replace sensors, batteries and sensor filters. That means long life and low cost.

- Complete with an extensive selection of sensor options. Count on comprehensive detection, whether you're monitoring for common or exotic hazards.
- The first single-gas...



Scan product



Ref: KT116017002HBWG

Honeywell BW Solo BLE Wireless Version O2 Gas Detector

Honeywell BW™ Solo
Serviceable Single-gas Detector

The easiest single-gas detector to service, with no need to take it apart to replace sensors, batteries and sensor filters. That means long life and low cost.

- Complete with an extensive selection of sensor options. Count on comprehensive detection, whether you're monitoring for common or exotic hazards.
- The first single-gas...



Scan product

Ref: KT116017002WLSD

Wireless Sounder

Wireless Sounder

Make: Textel

Model no: WSS



Scan product



Ref: KT116017002WLSD

Wireless Sounder

Wireless Sounder

Make: Textel

Model no: WSS



Scan product