



Product Catalogue

Fire Extinguishers

Safety > Fire Safety Solutions > Fire Extinguishers



KT Automation Private Limited · D 32-33 Kamalanjali Commercial Complex,
Radhakrishna Crossing, Akota · 390020 Vadodara



Ref: KTI07006001S4AB

Fire Extinguisher KANEX 4 kg ABC

KANEX ABC Type Fire Extinguisher Cap. 4 kg
Filled with Mono Ammonium Phosphate Powder
40% confirms to IS 14609.

Stored Pressure Type, UGTS Pressure Gauge,
Gross Weight 6.6 Kg, Empty Weight 2.6 Kg, Can
Height 490mm, Diameter 140 ± 10mm, Discharge
Time 18 Sec.

Controllable discharge mechanism, Jet Range 3
Meters, Average Discharge is 90%, applicable on
Class A,B & C and electrica...



Scan product



Ref: KTI07006001S2AB

Fire Extinguisher KANEX 2 kg ABC

KANEX ABC Type Fire Extinguisher Cap. 2 kg (
STORED PRESSURE) Filled with Mono
Ammonium Phosphate Powder 40%

Stored Pressure Type, UGTS Pressure Gauge,
Gross Weight 3.4 Kg, Empty Weight 1.4 Kg, Can
Height 380mm, Diameter 106 ± 10mm, Discharge
Time 8 Sec.

, Controllable discharge mechanism, Jet Range 2
Meters, Average Discharge is 90%, applicable on
Class A,B & C and electrical...



Scan product



Ref: KT107006001K450

Fire Extinguisher KANEX 4.5 kg CO2

KANEX 4.5 kg CO2 High Pressure Portable Fire Extinguisher, filled with Co2 Gas as per IS 15222

gross Weight 16.4, empty weight

11.9 Kg, Control discharge mechanism fitted with 1 Meter Wire Braided Hose & Flat Horn with Diffuser Nozzle for dispersed discharge of CO2, Discharge Time 12 Sec, Average Discharge is 95%.

Applicable on Class B, C and



Scan product

Ref: KT107006002ABC4

Fire Extinguishers ABC 4 Kg

Type ; Fire extinguisher

color : Red

size : 4 kg



Scan product



Ref: KT107006002ABC2

Fire Extinguishers ABC 2 Kg

Material : Iron

Ring Handle Mount

ABC Types Fire extinguishers are effective for all types of fire like Class A, B and C types of fires as well as Electrical fires and also ABC Powder Type (Stored Pressure) Fire Extinguisher, Multipurpose uses

Clear Instruction Label and No Maintenance required
operating temperature (-0) °C to (+55) °C



Scan product



Ref: KT107006001S6AB

Fire Extinguisher KANEX 6 kg ABC

KANEX ABC Type Fire Extinguisher Cap. 6 kg

Filled with Mono Ammonium Phosphate Powder

50% confirms to IS 14609

Stored Pressure Type, UGTS Pressure Gauge,

Gross Weight 8.9 Kg, Empty Weight 2.9 Kg, Can

Height 530 mm, Diameter 150 ± 10mm, Discharge

Time 24 Sec

Controllable discharge mechanism, Jet Range 5

Meters, Average Discharge is 90%, applicable on

Class A,B & C and electrical...



Scan product



Ref: KT107006002ABC1

Fire Extinguishers ABC 1 Kg



"Safety first" OR "Vintex" store pressure ABC type 1Kg. MAP base

Type : Fire extinguisher

Make : OEM

Color : Red

Weight : 1 kg

"ABC" indicating that they are designed to extinguish class A, B, and C fires. "BC" indicating that they are designed to extinguish class B and C fires.



Scan product

Ref: KT107006004CLEN

Fire Extinguisher 4 kg Clean Agent Refilling

Fire Extinguisher 2 kg Clean Agent (Refilling)



Scan product



Ref: KT107006002ABC6

Fire Extinguishers ABC 6 Kg

Fire extinguisher
Make : OEM
Type : ABC
Weight : 6 kg



Scan product

Ref: KT107006001S9AB

Fire Extinguisher KANEX 9 kg ABC

KANEX ABC Type Fire Extinguisher Cap. 9 kg
Filled with Mono Ammonium Phosphate Powder
50% conforms to IS 14609,
Stored Pressure Type, UGTS Pressure Gauge,
Gross Weight 13.3 Kg, Empty Weight 4.3 Kg, Can
Height 575 mm, Diameter 180 ± 10mm, Discharge
Time 31 Sec,
Gauge, Gross Weight 13.3 Kg, Empty Weight 4.3
Kg, Can Height 575 mm, Diameter 180 ± 10mm,
Discharge Time 31 Sec, Contro...



Scan product



Ref: KT107006002CO45

Fire Extinguishers Safety First Co2 4.5 Kg



Type CO2 Stored Pressure

Material-Gas carbon dioxide with discharge horn & control mechanism and body made from mild steel.

Features-Fire rating 21B. Discharge range 2 Meter.

Controlled Discharge, easy to service & rechargeable.

Approval-IS 15683

Application-Suitable for class B,C type fire. More suitable for flammable liquid, Gases,& Electrical started fire.



Scan product

Ref: KT107006001K2CO

Fire Extinguisher KANEX 2 kg CO2



KANEX 2 kg CO2 High Pressure portable Fire Extinguisher, filled with CO2 Gas as per IS 15222.

Gross Weight 8.2, empty weight

6.2 Kg, Control discharge mechanism fitted with Bend pipe and Discharge Horn, Discharge Time 9 Sec, Average Discharge is 95%,

Applicable on Class B, C and electrically started Fire, Fire Rating 8B, Internal coating is not applicable.

Valve Confirm to IS 3...



Scan product



Ref: KT107011001SFFE

Strike Fire Fire Extinguisher

Strike Fire – Fire Extinguisher
Portable Aerosol Fire Extinguisher



Scan product

Ref: KT107006003DCP6

Fire Extinguisher DCP 6 Kg Refilling

Refill of Existing Fire Extinguisher
6 KG DCP



Scan product



Ref: KT107006003DCP9

Fire Extinguisher DCP 9 Kg Refilling

Refill of Existing Fire Extinguisher
9 KG DCP



Scan product

Ref: KT107006001S6DCP

Fire Extinguisher 6 kg DCP

SODIUM BICARBONATE BASE POWDER Dry chemical powders are important fire fighting agents as they are stable, free flowing and easy to handle
Extinguisher media : DRY Powder IS 4308
Discharges Time Min.: 13 Seconds



Scan product



Ref: KT107006001S9DC

KANEX DCP type Fire extinguisher cap. 9 Kg



"KANEX" DCP type Fire extinguisher cap. 9 Kg.
filled with with Mono Ammonium Phosphate
KANEX MARQ-9-40% confirm to IS 14609

- Design-Hose & Nozzle
- Fire Rating (MAP-50%) - 6A : 183B
- Height (Approx.) - 585 mm
- Diameter (Approx.) -180 ± 5 mm
- Average Discharge time-31 Sec
- Average Range of throw-6 m
- Average % Discharge-94%
- Operating Temperature--30 °C to +60 °C
- Service/Ma...



Scan product

Ref: KT107006001S4CL

Fire Extinguisher KANEX 4 Kg Clean Agent



KANEX 4 kg Clean Agent Fire Extinguishers filled with HFC Based gas electrically nonconductive non corrosive, colorless and non-residual gas, Applicable classes A, B, C, and electrical fires, UGTS Pressure Gauge, Gross Weight 6.7 Kg, empty Weight 2.7 Kg, Can Height 490mm, Diameter 140 ± 10mm, Discharge Time 14 Sec, Controllable discharge mechanism, Jet Range 3.5 Meters, Average...



Scan product



Ref: KT107006003DCM9

Fire Extinguisher DCP Metal 6 Kg Refilling



Metal fire extinguisher Refilling
6 KG DCP (METAL)



Scan product

Ref: KT107006001MFFE

Mechanical Foam stored pressure type Fire Extinguisher KANEX KANEX 9 Ltr



KANEX 9 ltr. Mechanical Foam stored pressure type Fire Extinguisher filled with AFFF Foam confirms to IS 4989 (Part-II). Applicable fire class A & B, UTGS Pressure Gauge, Gross Weight 12 Kg, empty weight 4.3 Kg, Can Height 575mm, Diameter 180 ± 10mm, Discharge Time 35 Sec, Controllable discharge mechanism, Jet Range 7 Meters, Average Discharge is 95%, Fire Rating-4A:144B, Can ...



Scan product



Ref: KT107006001S9DCP

Fire Extinguisher 9 kg DCP

SODIUM BICARBONATE BASE POWDER Dry chemical powders are important fire fighting agents as they are stable, free flowing and easy to handle

Extinguisher media :DRY Powder IS 4308

Discharges Time Min.: 13 Seconds



Scan product

Ref: KT107006002CO2K

Fire Extinguishers Co2 2 Kg

Material-Gas carbon dioxide with discharge horn & control mechanism and body made from mild steel.

Features-Fire rating 8B. Discharge range 1 Meter. Controlled Discharge, easy to service & rechargeable.

Application-Suitable for class B,C type fire. More suitable for flammable liquid, Gases,& Electrical started fire.



Scan product



Ref: KT107006001DCP25

Fire Extinguisher DCP 25 Kg

DCP Fire Extinguisher Cap. 25 kg. filled with Mono Ammonium Phosphate Powder 50% confirm to IS 4308 Applicable fire classes A, B & C, Gross Weight 84 Kg, empty Weight Approx 59 Kg, Can Height 980mm, Diameter 300 ± 10mm, External CO2 gas Cylinder of 1 kg (PESO Approved), Discharge mechanism of EPDM Hose with SS spring of 300mm to avoid kink (3 meter long) & shut off nozzle, Disc...



Scan product

Ref: KT107006002ABC9

Fire Extinguishers ABC 9 Kg

Fire Extinguisher
Type : ABC
weight : 9 kg



Scan product



Ref: KTI07006001S6CL

Fire Extinguisher KANEX 6 Kg Clean Agent



KANEX KCARQ-6 CLEAN
AGENT TYPE FIRE EXTINGUISHER - 6KG
Clean Agent 6 kg Fire
Extinguisher filled with HFC
Based gas, Electrically
nonconductive noncorrosive,
colorless and non-residual gas, Applicable classes A, B, C,
and
electrical fires, UGTS PressureGauge, Gross Weight 8.9 Kg,
empty Weight 2.9 Kg, Can
Height 530mm, Diameter 150 Å± 10mm, Discharge Time
22Sec, Controllable dis...



Scan product

Ref: KTI07006001K9CO

Fire Extinguisher KANEX 9 kg CO2



KANEX 9 kg CO2 High Pressure trolley mounted Fire
Extinguisher, filled with Co2 Gas as per IS 15222.
Gross Weight 29 Kg, empty weight 20 Kg, Control discharge
mechanism fitted with 2 Meter Wire Braided Hose & Flat
Horn with Diffuser Nozzle for dispersed discharge of CO2,
Discharge Time 30 Sec, Average Discharge is 95%.
pplicable on Class B, C and
Design-Hose & Horn
• Fire Ratin...



Scan product



Ref: KT107006001S1AB

Fire Extinguisher KANEX 1 kg ABC

KANEX ABC Dry Powder Type Fire Extinguisher
Cap. 1 kg (STORED PRESSURE) Filled with
Mono Ammonium Phosphate Powder 50%
Stored Pressure Type, UGTS Pressure Gauge,
Gross Weight 2 Kg, Empty Weight 1 Kg, Can
Height 325mm, Diameter 86 ± 10mm, Discharge
Time 8 Sec, Controllable discharge mechanism,
Jet Range 2 Meters, Average Discharge is 90%,
applicable on Class A,B & C and electr...



Scan product

Ref: KT107006001S2CL

Fire Extinguisher KANEX 2 Kg Clean Agent

KANEX 2 kg Clean Agent Fire Extinguishers filled
with HFC Based gas electrically nonconductive non
corrosive, colorless and non-residual gas,
Applicable classes A, B, C, and electrical fires,
UGTS Pressure Gauge, Gross Weight 3.6 Kg,
empty Weight 1.6 Kg, Height 380mm, Diameter
106 ± 10mm, Discharge Time 12 Sec, Controllable
discharge mechanism, Jet Range 3 Meters,
Average Disch...



Scan product



Ref: KT107006001MF45

Mechanical Foam stored pressure type Fire Extinguisher KANEX KANEX 45 Ltr

KANEX 45 ltr. Mechanical Foam type Fire Extinguisher filled with AFFF Foam (6%), Applicable fire class A&B, Can Height 1000mm, Diameter 310 mm, Controllable Discharge mechanism, Discharge Time min. 30-160 Sec, Jet Range 9 Meters, Average Discharge is 90%, Fitted with EPDM Hose with SS spring of 300mm to avoid kink (4 meter long) & Air aspirated Nozzle, CO2 gas Cartridge of 300 ...



Scan product



Ref: KT107006001K650

Fire Extinguisher KANEX 6.5 kg CO2

KANEX 6.5 kg CO2 High Pressure trolley mounted Fire Extinguisher, filled with Co2 Gas as per IS 15222 Gross Weight 21 Kg, empty weight 14.5 Kg, Control discharge mechanism fitted with 1 Meter Wire Braided Hose & Flat Horn with Diffuser Nozzle for dispersed discharge of CO2, Discharge Time 20 Sec, Average Discharge is 95%. applicable on Class B, C and electrically started Fire, I...



Scan product



Ref: KT107006001K5MA

Fire Extinguisher KANEX 5 kg ABC Dry Powder Ceiling Mounted

KANEX 5 kg ABC Dry Powder Ceiling Mounted
Modular Type -MAP 50% Fire Extinguishers

- Design-Ceiling Mounted
- Height (Approx.)-375 mm
- Diameter (Approx.)-230 ± 10 mm
- Average Discharge time-6-8Sec
- Hanging height above risk-1.5 Mtr to 2 Mtr.
- Area Protection-2 to 2.5 m2
- Volume Protection-7 m3
- Average % Discharge-99%
- Operating Temperature--30 °C to +60 °C
- Service/Test Pressu...



Scan product

Ref: KT107006002C22K

Fire Extinguishers CO2 22.5 Kg

Fire extinguisher

Make : OEM

Type : CO2

Weight : 22.5 kg



Scan product



Ref: KT107006001K252

Trolley mounted Fire Extinguisher KANEX 25 Kg ABC Type

"KANEX" DCP trolley mounted Fire Extinguisher Cap. 25 kg. filled with Mono Ammonium Phosphate Powder 50% confirm to IS 4308 Applicable fire classes A, B & C, Gross Weight 84 Kg, empty Weight 59 Kg, Can Height 980mm, Diameter 300 ± 10mm, External CO2 gas Cylinder of 1 kg (PESO Approved), Discharge mechanism of EPDM Hose with SS spring of 300mm to avoid kink (3 meter long) & shut...



Scan product



Ref: KT107006001S4FC

Kanex 4 Ltr F Class WET Chemical Fire SS Body Type Fire Extinguisher

K Class Kitchen Wet chemical (Blend of Potassium Acetate, Potassium citrate or Potassium carbonate) 4 Ltr. Fire Extinguisher, Smooth and Polished Stainless Steel body, Applicable fire class K, UGTS Pressure Gauge, Can Height 550 mm, Diameter 150 ± 10mm, Discharge Time 13 Sec, Jet Range 2 Meters, Average Discharge is 95%, Controllable discharge mechanism with EPDM Hose & Specia...



Scan product



Ref: KT107006001S6DC

KANEX DCP type Fire extinguisher cap. 6 Kg



"KANEX" DCP type Fire extinguisher cap. 6 Kg.
filled with Mono Ammonium Phosphate Powder
50% confirm to IS 14609

- Design-Hose & Nozzle
- Fire Rating (MAP-50%) - 4A : 144B
- Height (Approx.) - 540 mm
- Diameter (Approx.) - 150 ± 5 mm
- Average Discharge time-24 Sec
- Average Range of throw-5 m
- Average % Discharge-94%
- Operating Temperature--30 °C to +60 °C
- Service/Max. service...



Scan product

Ref: KT107006001K06K

Trolley mounted Fire Extinguisher KANEX 6.5 KG CO2



KANEX 6.5 kg CO2 High Pressure trolley mounted
Fire Extinguisher, filled with Co2 Gas as per IS
15222, Gross Weight 25 Kg, empty weight 18.5 Kg,
Control discharge mechanism fitted with 1.5 Meter
Wire Braided Hose & Flat Horn with Diffuser
Nozzle for dispersed discharge of CO2, Discharge
Time 25 Sec, Average Discharge is 95%,
applicable on Class B, C and electrically started
Fire...



Scan product



Ref: KT107006001LI6S

KFLIHQ-6 Lithiumion Store Pressure Fire Extinguisher 6 kg



KANEX KFLIHQ-6 LITHIUMION STORED PRESSURE FIRE EXTINGUISHER -6 KG

Lithium Ion stored pressure Fire Extinguisher Cap. 6 ltr. filled with Water additive Aqueous Vermiculate Dispersion (AVD), UGTS Pressure Gauge, Discharge Duration- 120-130 sec, Range 2.5-3.5 m, CanHeight 530 mm, Diameter 150 Å± 10mm, Min. Discharge Time 13 Sec, Controllable discharge mechanism, applicable on Clas...



Scan product

Ref: KT107006001S4DC

Fire Extinguisher KANEX 4 kg DCP



A Dry Chemical Fire Extinguisher is the most common type used in Australia. It is also known as a DCP, BE, or ABE fire extinguisher. To determine if a fire extinguisher is a dry chemical type, one simply needs to look for the white band that runs around the tank.

Powder : sodium bicarbonate

SBC/PBC Chemical powder capable of fighting against class B,C & Electrically started fir...



Scan product



Ref: KTI07006001SSDC

Fire Extinguisher 75 kg DCP

KANEX KFDRQ-75-50% ABC FIRE EXTINGUISHER CAP

Brand : Kanex



Scan product

Ref: KTI07006001W9C

Fire Extinguisher KANEX 9 kg CO2 Water Type Stored Pressure

KFWSRQ-9

KANEX 9 ltr. Water type stored pressure Fire Extinguisher filled with water of TDS 3 to 4 PPM, Applicable fire class A, UTGS Pressure Gauge, Gross Weight 12 Kg, empty weight 4.3 Kg, Can Height 575mm, Diameter 180 ± 10mm, Discharge Time 35 Sec, Controllable discharge mechanism, Jet Range 7 Meters, Average Discharge is 95%, applicable on Class A, Fire Rating- 3A, Can Con...



Scan product



Ref: KT107006002ABC3

Fire Extinguishers Safety First ABC 4 Kg

ABC 4 kg Fire Extinguisher

ABC Dry Powder

Mkae ; OEM

Color: red

"ABC" indicating that they are designed to extinguish class A, B, and C fires. "BC" indicating that they are designed to extinguish class B and C fires.



Scan product

Ref: KT107006001K225

Fire Extinguisher KANEX 22.5 kg CO2

KANEX 22.5 kg CO2 High Pressure trolley mounted Fire Extinguisher, filled with Co2 Gas as per IS 15222, Gross Weight 66 Kg, empty weight 43.5 Kg, Control discharge mechanism fitted with minimum 1.5 Meter Wire Braided Hose & Flat Horn with Diffuser Nozzle for dispersed discharge of CO2, Discharge Time 37 Sec, Average Discharge is 95%, applicable on Class B, C and electrically sta...



Scan product



Ref: KT107006001K22K

Trolley mounted Fire Extinguisher KANEX 22.5kg CO2

KANEX 22.5 kg CO2 High Pressure trolley mounted Fire Extinguisher, filled with Co2 Gas as per IS 15222, Gross Weight 66 Kg, empty weight 43.5 Kg, Control discharge mechanism fitted with minimum 1.5 Meter Wire Braided Hose & Flat Horn with Diffuser Nozzle for dispersed discharge of CO2, Discharge Time 37 Sec, Average Discharge is 95%, applicable on Class B, C and electrically sta...



Scan product



Ref: KT107006001S2CS

Fire Extinguisher 2 Kg Clean Agent

OEM make
2 kg Clean Agent HFC 236fa Based
Gas, Stored Pressure Type Fire Extinguisher
• Design-Hose & Nozzle



Scan product



Ref: KT107006001S9FC

Kanex 9 Ltr. F Class WET Chemical Stored Pressure SS Body Type Fire Extinguisher

Kanex 9 Ltr. F- Class WET Chemical Stored Pressure SS Body Type Fire Extinguisher

- Capacity-9 Ltr
- Design-Hose & Nozzle
- Fire Rating- 8A : 40F*
- Height (Approx.)-610 mm
- Diameter (Approx.)-180 ± 5 mm
- Average Discharge time-30 Sec. •Average % Discharge-95%
- Operating Temperature-+5 °C to +55 °C
- Service/Max. service/Test Pressure-9 / 15 / 35 bar
- Expelling Agent-Nitrogen (UHP ...



Scan product



Ref: KT107006001S9KT

Fire Extinguisher KANEX 9 kg K Class Kitchen Wet chemical

KFKHQ-9

"KANEX" 9 Ltr. Fire Extinguisher K Class Kitchen Wet chemical (Blend of Potassium Acetate, Potassium citrate or Potassium carbonate), Smooth and Polished Stainless Steel body, Applicable fire class K, UGTS Pressure Gauge, Can Height 620 mm, Diameter 180 ± 10mm, Discharge Time 13 Sec, Jet Range 2 Meters, Average Discharge is 90%, Controllable discharge mechanism with EPD...



Scan product



Ref: KT107006002AB10

Fire Extinguishers ABC 10 Kg

Type : Fire extinguisher

Make : OEM

Type: ABC

Weight : 10 kg



Scan product

Ref: KT107006002CLN4

Fire Extinguishers Clean Agent 4 Kg

Fire Extinguishers Safety First Clean Agent

Type : Clean Agent

Make : OEM

Color : Red

Weight : 4 kg



Scan product



Ref: KT107006002CO65

Fire Extinguishers C02 6.5Kg

Material-Gas carbon dioxide. With discharge horn and control mechanism.

Features-It is ideal unit for electric fire and petroleum products and LPG gas. It is fitted with two wheel for easy movement.

Approval-IS:2878

Application-Suitable for class B & C type fire.



Scan product

Ref: KT107006002FHYT

Hydrostatic Testing For Fire Extinguisher

Hydrostatic testing is the process of pressure testing rechargeable fire extinguisher components—shell, cylinder, hose assembly, etc.—with a liquid, such as water, in order to ensure that it has no leaks or structural flaws



Scan product