



Product Catalogue

Sensor Tap

Automation > Hygiene Automation Solutions > Sensor Tap



KT Automation Private Limited · D 32-33 Kamalanjali Commercial Complex,
Radhakrishna Crossing, Akota · 390020 Vadodara



Ref: KT110002001ET07B

Sensor Tap Euronics ET 07B

WALL MOUNTED SENSOR TAP (BATTERY OPERATED)

Wall Mounted Sensor Tap

Model : ET07B



TECHNICALS:

Operation - Automatic Infra-Red Sensor

Inlet Pipe : Diameter G1/2"

Water Pressure - 1 to 1.5 Bar (Min 1 bar working pressure required)

Power - Battery(4 X AAA Duracell)

Sensing Range - 08 - 12cm

Finish - Chrome-plated

Recommended Installation Height From Basin - 12 Inches

Warranty ...



Scan product

Ref: KT110002001K20L

Sensor Tap Euronics KSDT20L

Euronics KSDT20L

Automatic Tap Cum Automatic Soap Dispenser (2in1)

Counter Mount

Operation : Automatic Infra-Red Sensor

Supply Volume Per Drop (Soap Dispenser) : 2ML

Liquid Volume (Soap Dispenser) : 1500ML

Detecting Distance : 09-20 cm (Soap Dispenser & Faucet)

Power : Electrical (AC 220V/50Hz)

Inlet Water Pressure : 1.5 to 4.0 Bar (Min 1 bar Working pressure required)

Materia...



Scan product



Ref: KT110002001NH02

Contactless Sensor Tap T 102

Model : T-102

Smart Contactless Automatic Sensor Tap(AC/DC)

Dimension : L-190, Distance of premix from bottom-100 mm,

Control Box: L-124 mm, W-90 mm, D-54 mm

Material : Chrome Plated Brass Metal Body

Power : 220V AC / DC 6V - 4xAA Alkaline Batteries

Application Area : Basin Mounted

Sensing Range : 150 mm Adjustable

Water Pressure : 0.02 Mpa-0.8 Mpa, *0.05 Mpa is minimum

Requi...

Specification

T-102 Tap is an Ergonomically Swan Neck Design. It offers touch free convenience

and ensuring reduces the spread of germs and bacteria. This Tap help prevent water wastage, saving ...



Scan product

Ref: KT110002001ET01

Sensor Tap Euronics ET 01BE

AUTOMATIC SENSOR TAP

Basin Mount Sensor Tap

Model : ET01BE

TECHNICALS:

Operation - Automatic Infra-Red Sensor

Water Pressure - 1 to 1.5 Bar (Min 1 bar working pressure required)

Power - Electrical(AC 220V, 50 Hz) + Battery(4 X AA Duracell)

Battery Consumption - 30,000 Shots (4 X AA Duracell Batteries)

Sensing Range - 09 - 20cm

Finish - Chrome-plated

Warranty - 1 year

FEATU...



Scan product



Ref: KT110002001ET04

Sensor Tap Euronics ET 04

Operation: Infrared Sensor
Control Box: Diameter Of 'inlet' Pipe: G1/2"
Control Box: Diameter Of 'outlet' Pipe: G1/2"
Water Pressure Range: 0.75 (Min) – 7 Bar (1 Bar Or Above
For Best Performance)
Dual Operation: Electrical + Battery
Voltage: Dc6v Or Ac220v-240v (6v Output)
Battery Consumption (Dc): 4xaa Alkaline Batteries (Up-to
1.5yr Lifespan)
Power Consumption: =0.3mw
Sensin...



Scan product

Ref: KT11000200TAD01

Automatic Tap Adaptor Tap Mount Model No ETAD01

Bottom Sensor: Water will start and stop when activated
Running Cycle: 1,00,000 times in one range
Battery Charging time: 4 Hours (Approx)
Water Temperature: 75 Degree C
Hydraulic Pressure : 0.05-0.8Mpa
Power Consumption: 0.2 MW
Waterproof: IPX6
Size: 60X 34X49 mm



Scan product



Ref: KT110002001D12L

Sensor Tap Euronics KSD12L

Automatic Tap Cum Soap Dispenser (2in1) Basin Mount
Note : Recommended height of Wall Mount Tap- 12 Inch from top of washbasin. 4 x AA Duracell Battery are given complimentary with all battery operated taps.
Black Color & Brush Gold cost extra



Scan product

Ref: KT110002001DT10

Sensor Tap Euronics KSDT10

Automatic Tap Cum Automatic Soap Dispenser (2in1), Basin Mount
Note : Recommended height of Wall Mount Tap- 12 Inch from top of washbasin. 4 x AA Duracell Battery are given complimentary with all battery operated taps.
Black Color & Brush Gold cost extra



Scan product



Ref: KT110002002ET05

Sensor Tap Euronics ET05 NW

Operation: Infrared Sensor

Control box: Diameter of 'inlet' pipe: G1/2"

Control box: Diameter of 'outlet' pipe: G1/2"

Water pressure range: 0.75 (Min) - 7 Bar (1 bar or above for best performance)

Dual Operation: Electrical + Battery

Voltage: DC6V or AC220V-240V (6V Output)

Battery Consumption (DC): 4xAA alkaline batteries (up-to 1.5yr lifespan)

Power consumption: =0.3mW

Sens...



Scan product

Ref: KT110002003ET06

Sensor Tap Euronics ET06 L

Operation: Infrared Sensor

Control Box: Diameter Of 'inlet' Pipe: G1/2"

Control Box: Diameter Of 'outlet' Pipe: G1/2"

Water Pressure Range: 0.75 (Min) - 7 Bar (1 Bar Or Above For Best Performance)

Dual Operation: Electrical + Battery

Voltage: Dc6v Or Ac220v-240v (6v Output)

Battery Consumption (Dc): 4xaa Alkaline Batteries (Up-to 1.5yr Lifespan)

Power Consumption: =0.3mw

Sensin...



Scan product



Ref: KTI10002003ET08

Sensor Tap Euronics ET08 VS

Operation: Infrared Sensor
Control Box: Diameter Of 'inlet' Pipe: G1/2"
Control Box: Diameter Of 'outlet' Pipe: G1/2"
Water Pressure Range: 0.75 (Min) – 7 Bar (1 Bar Or Above For Best Performance)
Dual Operation: Electrical + Battery
Voltage: Dc6v Or Ac220v-240v (6v Output)
Battery Consumption (Dc): 4xaa Alkaline Batteries (Up-to 1.5yr Lifespan)
Power Consumption: =0.3mw
Sensin...



Scan product

Ref: KTI1000200TAD02

Automatic Tap Adaptor Model No ETAD02

ETAD02 Automatic Tap Converter
Battery Capacity: 3.7V Lithium Ion Battery
Charging Specifications: Micro USB Charging(5V/500 – 1000 mA)
Standby Power Consumption: ≥ 0.2 mW
Sensing Range: Side:1-6cm; Bottom:1-10cm
Applicable Water Pressure: 0.05-0.8 MPa
Fitting Faucet Nozzle: Male M24*1/ Female M22*1
Environmental Temperature: 1-40°C
Environmental Humidity of Using: $\geq 95\%$ RH
Water...



Scan product