



Product Catalogue

Attendant Waiter Nurse Calling System

Automation > Office Automation Solutions > Attendant Waiter Nurse Calling System



KT Automation Private Limited · D 32-33 Kamalanjali Commercial Complex,
Radhakrishna Crossing, Akota · 390020 Vadodara



Ref: KTI0401200WNCCB

2 key Wall Mount Call Button S

Model No.K-W2-H

Wireless and very easy to install system.

2 key Functions: Call,Cancel.

Extended Call button cord.

Strong Signal strength upto 200 mts.

23A-12V battery ensures long life.

Working voltage: DC12V

Working current: 10mA

Use Frequency: 433.92mhz

Size Dimensions : 85*85*10mm



Wall mount Wireless Call Button(with 120cm flexible cord)
BED UNIT



Scan product

Ref: KTI0401200WNKH2

2 key Button S

Model No.K-H2

2Key , Call/Cancel)

100% Waterproof.

Wireless and very easy to install system.

2 key Functions: Call,Cancel.

Strong Signal strength upto 100 mts.

23A-12V battery ensures long life.

Working voltage: DC12V

Working current: 10mA

Use Frequency: 433.92mhz

Size Dimensions : 60*60*22mm.



Scan product



Ref: KTI0401200WNSK1

1 Key Wireless Call Button

1 Key Wireless Call Button

1 Key Function

Matt Finish

12 V 23 A Battery,



Scan product

Ref: KTI0401200WCBHS

Wireless Call Button Holder Stand

Holder for Wireless Call Button

Material: 2mm thick milky white acrylic.

Dimensions: 4 inches high (h) by 2.5 inches wide (w).

Includes two 4mm holes.



Scan product



Ref: KT10401200WNK2S

2 key Button K2

Model No.K2

2Key , Call/Cancel)

Wireless and very easy to install system.

2 key Functions: Call, Cancel.

Strong Signal strength upto 100 mts.

23A-12V battery ensures long life.

Working voltage: DC12V

Working current: 10mA

Use Frequency: 433.92mhz

Size Dimensions: 60*60*22mm.



Scan product

Ref: KT10401200WNPCB

Emergency pull cord Button washroom Unit S

Model No.KW1P

Wireless and very easy to install system.

2 key Functions: Call,Cancel.

Easy "CORD PULL" operation.

Strong Signal strength upto 100 mts.

23A-12V battery ensures long life.

Working voltage: DC12V

Working current: 10mA

Use Frequency: 433.92mhz

Size Dimensions : 85*85*10mm



Scan product



Ref: KT104012001TEXT

Wireless Patient Room Call Station Textel

Wireless Patient Room Call Station

Design: Modular switch type

- Service request button: 01(red colour)
- Service cancel button: 01 (green colour)
- Service pull cord: 01(optional)
- Operating voltage: 12V Battery
- Amp: Standby



Scan product

Ref: KT10401200WNCPS

Wireless Call panel with Power Adaptor S

Model No.:K-336

Durable aluminum alloy shell body.

Can work with 999 call buttons

3 groups call at same time.

Can Store upto 30 calls in queue.

Working voltage: DC12V~18V

Working current:



Scan product



Ref: KT1040120SLT1XBK

1 button, Cancel only black, Water resistant IPX8



1 button, Cancel only black, Water resistant (IP-X8)
 Excellent Performance and Reliability
 Attractive compact design
 Quiet Operations for Call and Response
 Easy Installation and Use
 Water Proof
 Battery life 18-24 Months



Scan product

Ref: KT10401200WK34S

Wireless Led Display K34S



Model No.: K-34-S
 Working Voltage : DC 12V 1A
 Modulation : AM
 Pairing Capacity : 250 Transmitters
 Call Displayed : 3 Group
 Call Capacity : 32
 Frequency : 433.92 MHz
 Digits Displayed : 4 (0000-FFFF)
 Wireless Led Display With Power supply- (4 Digit Three Group)
 30 Call Waiting.
 Size Dimensions : 295x170x60mm



Scan product



Ref: KT10401200SEWAR

Repeater for Nurse Calling System S

Repeater for System

Transmit signal through walls and over large areas.

Enhance Signal strength upto 250mts.

Working voltage: 12V

Working current:



Scan product

Ref: KT10401200WK14S

Wireless Call panel S

Model No.:K-14S

Durable sheet metal body.

Support response monitoring software

Can work with 499 call buttons


1 groups call at same time.

Can Store upto 32 calls in queue.

Working voltage: DC12V

Use Frequency: 433.92mhz

Size Dimensions : 225*165*40mm



Scan product



Ref: KT10401200WK10W

Monitor Panel signage

MODEL NO- K10WMD

Size 260 x 170 x 22 mm

Screen size 10.1

Resolution 1280 x 800 Px

OS Anroid 10.0

Memory 1GB RAM

Built-in-Speaker 2 X W

Stand Table top stand

Support Horizontal/Vertical

Interface WiFi / Bluetooth



Scan product

Ref: KT10401200WKRXW

Wireless Receiver Module WiFi

MODEL NO- KRX (WIFI)

Size 175 x 95 x 30 mm

Interface RF/ WiF

Working Voltage DC 12V 1A

Call capacity 250 Transmitters

Digit Display 001-999

Body type ABS Plastic

RF frequency 433.92 MHz



Scan product



Ref: KT104012001WNCS

Wireless Nurse Calling System 32 Patient

Wireless Attendant Calling Panel With 32 Flashing Indicators With Power Supply.



Scan product

Ref: KT10401200S23PC

Display Call cancel SM323PC

Model No :- SM323PC

Main Display with 2x3 FND (2 digits X 3 displays) 20 call memory



Scan product



Ref: KT10401200WK3LI

Three Colors ledlight reciever S

Model No.:K-3L-Light
 Seprate power supply.
 Different color for different service types.
 Installed on wall or roof.
 Working voltage: DC12V
 Working current:



Scan product

Ref: KT1040120SLTSB62

Call Cancel button Transmitter with pullstring1 m SB62XWHS SB63XWHS

Call / Cancel button (Transmitter) with pullstring(1 m)
 The battery life 1 - 3 years
 The length of the twisted pull cord is up to one meter
 Used in Toilet / Wash room
 Separate Cancel button available



Scan product



Ref: KT10401200SLTCB

2 key Wall Mount Call Button SB9 2XWH

Model No:- SB9-2XWH

2 buttons (1 call+1 cancel) WH-white. Water resistant(IP-68)

SIZE 74W×46L×11H (mm)

WEIGHT about 28g

COLOR Snow White

RF Transmitter(FSK Low Power Data Transmission Standard)

FREQ 400Mhz Band

BATTERY CR2032 Coin cell 2EA

ANTENNA PCB Antenna

OTHER DETAIL Transmission Type : Omnidirectional (360°)

Warranty:- 1 Year



Scan product

Ref: KT1040120SLTSB71

1 button, Paired Cancel only black, Water resistant(IP X8)

1 button, Paired Cancel only black, Water resistant(IP-X8)

Excellent Performance and Reliability

Attractive compact design

Quiet Operations for Call and Response

Easy Installation and Use

Water Proof

Battery life 18-24 Months



Scan product



Ref: KT104012001SWW

Wrist watch S

Model No.:K-500 Plus

Can work with 500pcs 1-key and multi-key buttons.

Fast rechargeable and long life battery.

Indicate different service type via words.(call;bill;drink;etc).

3 reminder modes:: Light, Sound, Vibration.

Record when call come in and count of call.

Can store 50 calls and track the history.

Size Dimensions : 50*41*16mm



Scan product

Ref: KT10401205LT10RG

Corridor lamp

Wall-mount type corridor lamp (Receiver) 7-lighting colours available (colour selectable)

Single light with 6 colours

Different colours for the different call types

Can be configured with 20 Call Points

Common Light for Twin Sharing to reduce Investment

Light Steady / Blinking (Flashing) Configuration

Beep sound on or off



Scan product



Ref: KT10401200SLTRE

Repeater for Nurse Calling System SOLT

Modal No :- SR5-BPR

Transceiver (Receiver & Transmitter) max. output 10mW

Repeater for Nurse calling System



Scan product

Ref: KT10401200WSLTD

Display Call cancel SM3 33PC

Model No :- SM3-33PC

2Key , Call/Cancel)



100% Waterproof.

Wireless and very easy to install system.

2 key Functions: Call,Cancel.

Strong Signal strength upto 100 mts.

23A-12V battery ensures long life.

Working voltage: DC12V

Working current: 10mA

Main Display with 3x3 FND (3 digits X 3 displays),

20 call memory

Warranty:- 1 Year



Scan product



Ref: KT1040120SLT5BPR

Transceiver (Receiver & Transmitter) max. output 10mW (Repeater)

Transceiver (Receiver & Transmitter) max.
output 10mW

Extending the signal range

LCD display: Easy configuration

Avoid duplication of the same calls

Register up to 999 Call Buttons

Power supply: AC110~240V, DC12V/1A adaptor



Scan product

Ref: KT10401200SLTRP

SR5MPRT for PC Monitoring SOLT

SR5-MPRT for PC Monitoring

Windows 10 or 11 with speaker and working USB port should
be provided by the customer.

Frequency: 434.6500 MHz

Frequency stability: +/- 10 ppm

Data rate: 1800 bps

Channel space: 12.5 KHz

Modulation: FSK(+/- 3KHz)


Antenna Type: Helical type (internal)

PC interface: RJ45 to USB

Screen: LCD 1.3

Power/frequency: 10 mW.

Indicators: 2 LEDs (PWR/Rx indicator)...



Scan product



Ref: KT10401200W0KWC

Wireless Nurse Call System KWCS

Wireless Nurse Call System KWCS
 Live Call Popup
 Life time Data stored
 Color coding for delayed calls
 Export report in excel
 Live call timers
 Performance comparison chart



Specification

The Wireless Nurse Call System is designed to provide fast and reliable communication between patients and caregivers in hospitals, clinics, nursing homes, and assisted living faci...



Scan product

Ref: KT10401200WNK3L

110 DB Siren With Three Color light S

110 DB Siren With Three Color light
 To be used with Wireless panic alarm system.



To handle panic situations.
 Avoid accidents.
 Discrete communication.
 Wireless installation.
 Modular & flexible systems.
 Low maintenance cost system.
 Technology oriented and user friendly.



Scan product



Ref: KT104012001SLTW

Wrist watch SP7 100

Modal No :- SP7-100

Wrist-watch type mobile

Receiver Water resistant(IP-X7)



Created by immaizer.com



Scan product

Ref: KT10401200333PM

Display Call cancel SM333PN

Main Display with 3x3 FND (3 digits X 3 displays)



Scan product



Ref: KT10401200361PC

Display Call cancel SM361PC

Main Display with 6x1 FND (6 digits X 1 display), 20 call memory



Scan product

Ref: KT10401200SLTPC

Emergency pull cord Button washroom Unit

Model No :- SB6-2XWH-S
Emergency Pull Cord Button (Washroom Unit)
Call / Cancel button (Transmitter) with pull-string(1 m)
Warranty:- 1 Year



Scan product



Ref: KT10401200SM323

Display Call cancel SM323JC

Calls are stored from the 1st place(top left)-
2nd place(top right)-
3rd place(bottom right)... from 4th calls are
hidden in order(till 47 calls).



If cancel button is pressed from Call Point, the
responding call is deleted regardless of the
order of the call

If Cancel Only button is pressed, the 1st call is
deleted, then 2nd call display takes the place
of the 1st call, ...



Scan product

Ref: KT10401200W5LTB

Call/Cancel Button SB5R-2XWH-1PSR

Model : SB5R-2XWH-1PSR

Call / Cancel button.Cancellation by long press of button.
With 1 PSR cable.



Scan product



Ref: KT10401200W5LTH

CallCancel Button SB5R2XWH

SB5R-2XWH

Call / Cancel button. Cancellation by long press of button
Includes Mounting cover



Scan product

Ref: KT10401200WAW4H

Wireless Nurse Call System KW4H

Wireless Nurse Call System KW4H

Size: 85x85x10mm

Modulation: AM

Working Voltage: DC 12V

Working Current: 10mA

Radiated Power (ERP): 2.58 – 3.69 mW

Battery Type: 23A12V

Key Options: H.Keeping / Nurse / Code Blue

Frequency: 433.92 MHz

Transmitted Distance: 100 mt

Specification

The Wireless Nurse Call System is designed to provide fast and reliable communication between patients and caregivers in hospitals, clinics, nursing homes, and assisted living faci...



Scan product



Ref: KTI0401200WK12S



Ref: KTI0401200WK13S

Wireless Nurse Call System k13s eco



Specification

The K13S ECO Wireless Nurse Call System enables patients to quickly request assistance through wireless call buttons, improving caregiver response times and patient safety. It is i...





Ref: KT10401200WNK2P

Button Stand

Modal No - K-SP
Button Stand



Scan product

Ref: KT10401200WNKH4

4 key Button S

Wireless Call Button 4 Key
Call/Drink/Bill/Cancel
100% Waterproof.
Wireless and very easy to install system.
4 key Functions: Bill, Drink, Call, Cancel.



23A-12V battery ensures long life.
Working voltage: DC12V
Working current: 10mA
Use Frequency: 433.92mhz
Size Dimensions : 60*60*22mm



Scan product



Ref: KT10401200WSLTB

2 key Wall Mount Call Button SB6 3XWH P, PS


Model No SB6-3XWH-1PSR

Wall mount Wireless Call Button(with 120cm flexible cord)
BED UNIT

Call / Cancel button (Transmitter) with curled (P) or straight (PS)

1 PSR Cable with hand unit. Compatible with SB5 and SB6
cabled push-button 2X : call/cancel, 3X : 2 call/cancel

Warranty:- 1 Year



Scan product

Ref: KT10401200WUCPS

Wireless Call panel with USB with Power Adaptor S

Model No.:K-4CUSB

Durable metal body.

Support response monitoring software

Can work with 450 call buttons

3 groups call at same time.

Can Store upto 32 calls in queue.

Working voltage: DC12V

Use Frequency: 433.92mhz

Size Dimensions : 290*155*40mm



Scan product



Ref: KT10401200WUK14

Wireless Nurse Call Panel Four digit K14S



Wireless Nurse Call Panel Four digit K14S

Size 295X145X50mm

Modulation AM

Working Voltage DC12V1A

Frequency 433.92MHz

Body Type Sheet Metal

Pairing Capacity 250 Transmitters

Calls Displayed 1 Group

Wall mount

Support Software

Delay reminder

250 transmitters

Call Capacity 32

Digital Displayed 000-FFFF

Specification

Discrete communication between nurses and patients.

Long cord call button for serious patients.

Wireless personal/nurse wrist monitor.

Easily handle emergency situations.

Easy ...



Scan product

Ref: KT1040120SLT10FM

Mat Sensor

Call / Cancel button (Transmitter) with foot step-button cable (1.4 m)

The battery life 1 - 3 years

The length of the twisted pull cord is up to one meter

Used in Toilet / Wash room

Separate Cancel button available



Scan product



Ref: KT1040120SLT1PWH

1 button white Water resistant IP68

1 button white Water resistant IP68
 Excellent Performance and Reliability
 Attractive compact design
 Quiet Operations for Call and Response
 Easy Installation and Use
 Water Proof
 Battery life 18-24 Months*



Scan product

Ref: KT1040120SLT1WHP

Paired Cancel only button BK black, WH white SB51XBKWH Paired

Paired Cancel only button BK black, WH white SB51XBKWH
 Paired
 Excellent Performance and Reliability
 Attractive compact design
 Quiet Operations for Call and Response
 Easy Installation and Use
 Water Proof
 Battery life 18-24 Months



Scan product



Ref: KT1040120SLT1XWH

Cancel only button BKblack, WHwhite SB51XBKWH

Cancel only button - BK-black, WH-white
Excellent Performance and Reliability
Attractive compact design
Quiet Operations for Call and Response
Easy Installation and Use
Water Proof
Battery life 18-24 Months



Scan product

Ref: KT1040120SLT2PWH

2 buttons 2 call WHwhite Water resistantIP68 SB92PWH

2 buttons (2 call) WH-white. Water resistant(IP-68)
SB9-2PWH
Excellent Performance and Reliability
Attractive compact design
Quiet Operations for Call and Response
Easy Installation and Use
Water Proof
Battery life 18-24 Months*



Scan product



Ref: KT1040120SLT2XWH

Call Cancel button Cancellation by long press of button Without cable SB52XWHBK



Call Cancel button Cancellation by long press of button
Without cable SB52XWHBK
Excellent Performance and Reliability
Attractive compact design
Quiet Operations for Call and Response
Easy Installation and Use
Water Proof
Battery life 18-24 Months



Scan product

Ref: KT1040120SLT3PWH

3 buttons WH white. Water resistant(IP-68) SB9 3PWH



3 buttons WH-white. Water resistant(IP-68)
Excellent Performance and Reliability
Attractive compact design
Quiet Operations for Call and Response
Easy Installation and Use
Water Proof
Battery life 18-24 Months*




Scan product



Ref: KT1040120SLT3XBK

2 buttons 1 call 1 cancel BK black, WH white Compatible with 1 PSR, 2 PSR SB62XBKWH or SB6 3XBKWH



2 buttons (1 call + 1 cancel)..BK-black, WHwhite. Compatible with 1 PSR, 2 PSR
 Straight / spiral cable (optional)
 Elegant yet rugged
 Wireless
 Battery life 18 - 24 months+ *
 Customised Call Type
 Can be integrated with multiple display panels
 Can be integrated with door light



Scan product

Ref: KT1040120SLT3XWH

3 buttons 2 call1 cancel WHwhite Water resistantIP68 SB93XWH



3 buttons (2 call+1 cancel) WH-white. Water resistant(IP-68) SB9-3XWH
 Excellent Performance and Reliability
 Attractive compact design
 Quiet Operations for Call and Response
 Easy Installation and Use
 Water Proof
 Battery life 18-24 Months*



Scan product



Ref: KT1040120SLT5MPR

Monitoring Receiver

PC Monitoring device (Receiver) with Solt basic monitoring programs

Call Displayed on PC Screen
 Different sounds for different call types
 Different background colours for different call types
 Call Escalation
 Reporting
 Power supply: AC110~240V, DC12V/1A adaptor



Scan product

Ref: KT1040120SLT6PBK

6 buttons call buttons, Kitchen Bell Compatible with 1 PSR, 2 PSR, 3 PSR SB66PBKWH

6 buttons call buttons, Kitchen Bell Compatible with 1 PSR,
 2 PSR, 3 PSR SB66PBKWH
 Straight / spiral cable (optional)
 Elegant yet rugged
 Wireless
 Battery life 18 - 24 months+ *
 Customised Call Type
 Can be integrated with multiple display panels
 Can be integrated with door light



Scan product



Ref: KTI040120SLT6PSR

1PSR Cable with hand unit SOLT


1PSR Cable with hand unit
Compatible with SB5R, SB6
Includes Bed hook
PSR cable - 5feet - 150 mm + 1050 mm straight and rest
coiled



Scan product

Ref: KTI040120SLT6XBK

6 buttons5 call1 cancel or 3 call3 cancel
Compatible with 1 PSR, 2 PSR, 3 PSR
SB66XBKWH



- 6 buttons(5 call/1 cancel or 3 call/3 cancel). Compatible with 1 PSR, 2 PSR, 3 PSR SB6-6XBK/WH
- Straight / spiral cable (optional)
- Elegant yet rugged
- Wireless
- Battery life 18 - 24 months+ *
- Customised Call Type
- Can be integrated with multiple display panels
- Can be integrated with door light



Scan product



Ref: KT1040120SLTB62X

Call Cancel button Transmitter with foot stepbutton cable 14 m

Call / Cancel button (Transmitter) with foot step-button cable (1.4 m)

The battery life 1 - 3 years

The length of the twisted pull cord is up to one meter

Used in Toilet / Wash room

Separate Cancel button available



Scan product

Ref: KT1040120SLTPBK

1 button, black, Water resistantIPX8

1 button, black, Water resistant(IP-X8)

Excellent Performance and Reliability

Attractive compact design

Quiet Operations for Call and Response

Easy Installation and Use

Water Proof

Battery life 18-24 Months*



Scan product



Ref: KT1040120SLTSB52

Call only button BK black, WH white SB51PBKWH



Call only button - BK-black, WH-white
Excellent Performance and Reliability
Attractive compact design
Quiet Operations for Call and Response
Easy Installation and Use
Water Proof
Battery life 18-24 Months



Scan product

Ref: KT1040120SLTSPBKT

1 button, black, air touch call Water resistantIPX8 SB71PBKT



1 button, black, air-touch call Water
resistant(IP-X8)
Excellent Performance and Reliability
Attractive compact design
Quiet Operations for Call and Response
Easy Installation and Use
Water Proof
Battery life 18-24 Months



Scan product



Ref: KT1040120SLTWCB

2 key Wall Mount Call Button SB7 2XBK

Model No:- SB7-2XBK

Tipo de frecuencia: FSK (exactitud y confiabilidad)

- Batería: 2 x CR2032

- CPU TI: el cual cuenta con su propio protocolo de comunicación.

- ID del botón: 16 millones de ID's disponibles.

- Diseño lujoso: con chasis de uretano.

- Impermeable: Certificado IP-65.

- Indicador de llamada: LED rojo en la parte superior y en el contorno del botón.

- 2 colores di...



Scan product

Ref: KT1040120SLTWCS

Waiter call system SB9 3XWH

Model No:- SB9-3XWH

Waiter call system

Call button

Drink Button

Cancel button

Call-cancel 3 buttons (2 call + 1 cancel)..WH-white



Scan product