



Product Catalogue

Flame Proof Speaker

Automation > PA Solutions > Flame Proof Speaker



KT Automation Private Limited · D 32-33 Kamalanjali Commercial Complex,
Radhakrishna Crossing, Akota · 390020 Vadodara



Ref: KT1140040074025

Flameproof Horn Speaker ATS 4025 IIC

Flameproof Weatherproof Horn Loud Speaker

Rated wattage: 30 watts

Rated voltage: 15.5 Volts

Rated SPL at 1 khz, 15 watts at 1 mtr : 117 db

Effective freq response: 500 Hz to 5500 Hz (typical)

Dimension: 445mm (length) X 280mm (height)

Colour: Orange

SS bracket

Climatic

Temperature class : T6

Relative humidity : 95 %

IP protection : IP 65

Material

Flameproof unit cast Aluminium...



Scan product

Ref: KT114004007002

Flameproof Wall Mounting PA Station ATS 7002

Transmit Section

Input sensitivity 3mV

Rated output voltage 2V rms across 240 ohm

Distortion < 1% @ 1 KHz

S / N ratio < -50dB (unweighted)

Power Amplifier Section

Input sensitivity 2V rms

Input impedance 230 ohms

Rated power output 30 W (P) in 8 ohms

Rated load impedance 8 or 16 ohm

Distortion < 1 % @ 1KHz

S / N ratio Better than 50 dB

Volume control settings Internal taps for

...



Scan product