



Product Catalogue

Slave Reader

Automation > Access Control, Attendance System > Slave Reader



KT Automation Private Limited · D 32-33 Kamalanjali Commercial Complex,
Radhakrishna Crossing, Akota · 390020 Vadodara



Ref: KT101001001NFR12

NFR12 Reader Fingerprint Reader, Cards Slave reader Biomax

Features

Sensor - Optical Sensor
Communication - RS 485
Optional Features - Mifare
Card Reader - YES
Speaker - Yes
Working Voltage - 12V DC
Operating Temperature - 0°C - 45°C
Operating Humidity - 20% - 80%
Dimension - 55*105 mm
Warranty - 1 Year Onsite



Scan product

Ref: KT101001001SF12

F12 Reader Fingerprint Reader, Cards Slave reader Biomax

Features

Sensor - Optical Sensor
Communication - RS 485
Optional Features - Prox / Mifare / HID card reader
Voice Prompt - Buzzer
Working Voltage - 12V DC
Operating Temperature - 0°C - 45°C
Operating Humidity - 20% - 80%
Dimension - 48 mm x 100 mm x 37 mm
Warranty - 1 Year Onsite



Scan product



Ref: KTIO1001001C10

Card Registration CR10MW

Mater Read Range: Upto5cm
Power/Current: USB5VDC/Max80mA
LED Indicator: 2Color LED indicators
(Red&Green)
Beeper:Yes
OperaΘng Frequency: 13.56 MHz
OperaΘng Temperature:0°C-70°C
OperaΘng Humidity:10%-90%(relaΘve
humiditynon-considered)
Material:ABS+PCwithtexture
Dimension(WxHxT):140x 100x 30mm
Weight: 120g
Power by USB.
LED indicator and buzzer feedback



Scan product

Ref: KTIO1001001EF75

7500 USB Scanner for FP Registration

Features
Type of Product : Fingerprint Based System
Sub Type : Fingerprint USB reader
Communication Type : USB

To register FP in system while using slave readers only.



Scan product



Ref: KT101001001KR26

KR26E Slave Reader with Attendance and multi door access control

Model : KR26E
Wigand 26 Reader ,Miface 13.56 MHZ
Card Type : EM
Working Voltage : DC12V
Reading Range : 2-5CM
Case Type : Plastic Case
Wiegand Interface :WG26/34
Communication Distance : 100 m
Dimension ; 45x110x20 mm



Scan product



Ref: KT101001001KR50

KR503 E, M Slave Reader with Attendance and multi door access control

KR503E - 125KHz Proximity card reader
KR503M - 13.56MHz Mifare card reader
Read Range - KR500E - Up to 10CM , KR503M - Up to 5CM
Reading Time (Card) - ≤300ms

Power / Current - DC 6-14V / Max.70mA
Connectivity - Wiegand
Input Port - 2ea (External LED Control
Output Format - 26bit Wiegand (default) / 34bit Wiegand (default)
LED Indicator - 2 Color LED Indicators(Red and Green)
B...



Scan product