



Product Catalogue

Wifi Cameras Hikvision IP CCTV System

Security > CCTV Surveillance System > IP CCTV System > Hikvision IP CCTV System > Wifi Cameras Hikvision IP CCTV System

KT Automation Private Limited · D 32-33 Kamalanjali Commercial Complex,
Radhakrishna Crossing, Akota · 390020 Vadodara

Ref: KT103006002HWF

Wifi Camera Hikvision

Support Wi-Fi.



Scan product

Ref: KT103006002HK20

IP Cube Camera 2MP Hikvision

Up to 2 Megapixel (1920 × 1080 @ 30 fps) Resolution
IR Range Approx 10 Meters
Built-in Microphone and Speaker
Built-in Micro SD/SDHC/SDXC Card Slot, up to 128 GB



Scan product

Ref: KT103006002EC8C

Outdoor Pan, Tilt Wifi Camera C8C EZVIZ



Model No.:C8C

Outdoor Pan/Tilt Camera

Operating Conditions -30°C ~ 60°C (14 °F to 113 °F),

Humidity 95% or

less (non-condensing)

IP Grade IP65

Dimensions 158 x 157 x 149 mm (6.22 x 6.18 x 5.87 inch)

Power Supply DC 12V / 1A

Power Consumption MAX. 6 W

Packaging Dimensions 197 x 185 x 205 mm (7.76 x 7.28 x 8.07 inch)

Weight (With Package) 885 g (31.22 oz)

Net Weight 510 g (17.99...



Scan product

Ref: KT103006001OPH8

Outdoor PTZ Camera Ezviz H8 Pro 2K

Model CS-H8-R100-1H3WKFL

Image Sensor 1/2.7" Progressive Scan CMOS

Shutter Speed Self-Adaptive shutter

Lens 4mm @ F1.6, Viewing angle: 46° (Vertical), 89°

(Horizontal), 104° (Diagonal) 6mm @ F1.6, Viewing

angle:28° (Vertical), 54° (Horizontal), 62° (Diagonal)

PT Angle Pan: 340°, Tilt: 80°

Minimum Illumination 0.5 Lux @ (F1.6, AGC ON), 0 Lux with

IR (Data is obtained from EZVIZ ...



Scan product

Ref: KT10300600TY1W

Wifi Camera Hikvision Smart Wi Fi Pan, Tilt Camera



Model : CS-TY1-B0-1G2WF
Make : Hikvision
Image Sensor : 1/3" Progressive Scan CMOS
Shutter Speed: Self-adaptive shutter
Lens : 4mm@ F2.4, view angle: 85° diagonal, 75° horizontal, 45° vertical
Lens Mount : M12
Video Compression : H.264
Storage MicroSD card slot (Max. 256GB)
Power Micro USB
Wired Network RJ45 X 1 (10M/100M self-adaptive Ethernet port) Standard IEEE802.11b/g/n
Fre...



Scan product

Ref: KT103006002EZVI

IP 2 Way Audio EZVIZ Camera



Camera type Bullet camera
Sensor size 9.4 mm (1/2.7")
Sensor type CMOS
Max. viewing angle hor. 103 °
App compatibility Yes
Transfer type Wi-Fi
Wi-Fi standard IEEE802.11b , IEEE802.11g , IEEE802.11n
IR range (max.) 30 m
Used at Outdoors
Type microSD card (up to 128 GB)



Scan product

Ref: KT103006003HWF

2 MP Wifi Camera Hikvision

Model No. DS-2CD3123G0E-I(W)

2 MP IR Fixed Dome Network Camera

□ 1/2.8" Progressive Scan CMOS

□ 1920 × 1080@30fps

□ 2.8/4/6 mm fixed lens

□ Color: 0.01 Lux @(F1.2, AGC ON), 0.028Lux @(F2.0, AGC ON);

□ H.265+, H.265, H.264+, H.264

□ 120 dB WDR

□ 2 Behavior analyses

BLC/3D DNR/ROI/HLC

□ Built-in micro SD/micro SDHC/micro SDXC card slot, up to 128 GB



Scan product

Ref: KT10300600TYDCW

Wifi Camera C4S features a vandal proof dome

Model - CS-C4S-52(W) EFR (4mm)

Image Sensor - 1/3" Progressive Scan CMOS

Minimum Illumination - 0.02 lux @(F2.0, AGC ON), 0 lux with IR

Shutter Speed Self-adaptive shutter

Lens - 4mm@ F2.0, Horizontal angle : 90° Diagonal angle 107.5°

Lens Mount - M12

Day & Night - IR-cut filter

DNR - 3D DNR

WDR - Digital WDRVideo Compression H.264

H.264 Type - Main profile

Video Bit Rate HD, B...



Scan product