



Product Catalogue

Tripod Mounted searchlight

Security > LED Searchlights > Tripod Mounted searchlight



**Tripod Mounted Revolving LED
search light 250Watt**

KT Automation Private Limited · D 32-33 Kamalanjali Commercial Complex,
Radhakrishna Crossing, Akota · 390020 Vadodara



Tripod Mounted Revolving LED
search light 250Watt



Watch video

Ref: KT11200500TRPC30

Tripod Mounted Revolving LED search light 300 Watt

300W and 700 Meter range

SALIENT FEATURS

230 v supply

- Instant glow by power LED.
- Beam range more than 700 meters.
- Powerful narrow beam upto 5 degree.
- Life more than 1,00,000 burning hrs.
- Suitable to fit in various stands as per use.
- High reflectivity mirror back lens cum reflector

Manually operated, suitable for mounting of search-lights inside / outside of watch...



Scan product

Ref: KT11200500TRPC25

Tripod Mounted Revolving LED search light 250Watt

250W and 500 Meter range

SALIENT FEATURS

- Instant glow by power LED.
- Beam range more than 500 meters.
- Powerful narrow beam upto 5 degree.
- Life more than 1,00,000 burning hrs.
- Can be operated by Battery/Solar (optional).
- Suitable to fit in various stands as per use.
- High reflectivity mirror back lens cum reflector

Manually operated, suitable for mounting of search-l...



Scan product



Tripod Mounted Revolving LED
search light 250Watt



Ref: KT11200500MR30W

Revolving Search Light with Tripod 250W

Revolving Search Light Material Aluminium

Body Material - Aluminium

Power - 250w

Light Color - Cool White

Light Type - High intensity, Discharge LED

IP rating - IP66

Voltage - 90-300VAC, 50-60Hz

Beam Range -400+ Meters

PF - >0.95

Rotate - 360

minimum Height of tower -3M

CCT-5500K-6000K

Optical Grade: Rect or /Lens

Narrow Beam 3 Degree

Reflector /Lens Efficiency ->90%

Revolving Search Light

Body Material	ALUMINIUM
Power	250W
Lighting Color	Cool White
Lighting Type	High intensity Discharge LED
IP Rating	IP66
Working Voltage	90-300VAC, 50-60Hz
Features	High Intensity Beam, Projection Beam, High Glow Ratio
Beam Range	400+ Meters
PF	>0.95
Rotate	360°
Minimum Height of Tower	3M
CCT	5500K-6000K
Optical Grade	Rect or /Lens
Narrow Beam	3°
Reflector /Lens Efficiency	>90%



Scan product