



Product Catalogue

Automatic Rising Hydraulic Bollard

Automation > Automatic Entry Solutions > Automatic Rising Hydraulic Bollard



KT Automation Private Limited · D 32-33 Kamalanjali Commercial Complex,
Radhakrishna Crossing, Akota · 390020 Vadodara



Ref: KTI02001001BGHB

BGI K4 Crash Rated Hydraulic Bollard

BGI K4 Crash Rated Hydraulic Bollard

Model no.B3150

Accessories : Including control panel, Push button
,photosensor for humansafety,High Range Reciver,
High Range Remote Control,Loop detector



Drive Hydraulic
Cylinder Diameter 220 mm
Cylinder Length 700 mm
Rating K4 Rating
Cylinder Material ST 37
Special Stainless Steel cover SS 304
Cylinder Surface Treatment Hot Dip galvanized...



Scan product

Ref: KTI02001001MCHB

Hydraulic Bollard KTI K4 Rating

Make: Mcvick

Rating: 4k

Bollard Height: 600-1200 Mm

Bollard Diameter: 220 -273 Mm

Dimension Outdoor Finish:1600*1200*600

Wheel Load: 100 Kn

Load Impact:approx. 100 Kn

Vertical Load: 100 Kn Vertically(20 T)

Operation Time: Raising 4-6 Sec & Lowering 4-5 Sec

Operating Panel:from Both Side of Bollard Through Push
Button With Key Switch Control and From Remote Control
Upto 10 Meter...



Scan product



[Watch video](#)



Ref: KT1020020K4BBS8

K8 Crash Rated Bollards

Swaraj's K8 Crash Rated Bollards

Model: S8

Diameter: 275 with 3mm SS 304 Cover

Height: 1000mm

Mechanism:Hydraulicwith3secEFOand1CycleAccumulator
(01 Set = 05 Bollards)



Scan product

Ref: KT1020020K4BLRD

BOLLARDS, S4 Bollard

Model No : S4

Drive Unit - Hydraulic (S4-H) and Pneumatic (S4-P)

Drive Unit Hydraulic/Pneumatic

Rating K4/IWA 14-12013 Bollard V/7200 [N2A] 48/90/0.1

Diameter 223 mm

Height 900 mm

Model No S4

Certifications Physical Crash Test Certificate from MIRA
U.K.,CE,ISO 90012015



Scan product



Ref: KT1020020K4BST4

BOLLARDS, ST4 Bollard

Model No : ST4

Drive Unit - Hydraulic /Pneumatic

Drive Unit Hydraulic/Pneumatic

Rating K4/IWA 14-12013 Bollard V/7200 [N2A] 48/90/0.1

Certifications Physical Crash Test Certificate from MIRA



Scan product

Ref: KT102002J355M50

Hydraulic Bollard FAAC k12 Rated J355 HA M50

Model No.:J355 HA M50

Retractable security bollard

Type of Operator - Hydraulic Operator

Cylinder height from ground - 1200 mm

Cylinder diameter - 355 mm

Tested according to PaS 68 and IWA 14-1 Standards

Capable of arresting a truck traveling at 80 km/h in single unit configurations

Hydraulic control unit integrated in the bollard

Also available in EFO (Emergency Fast Operatio...



Scan product