



Product Catalogue

Guard Tour System

Security > Corporate Solutions > Guard Tour System



KT Automation Private Limited · D 32-33 Kamalanjali Commercial Complex,
Radhakrishna Crossing, Akota · 390020 Vadodara



Ref: KT104008001CPHL

Checkpoints for Guard Tour System 125Khz

Model No: 70A

Make : JWM

□ Frequency: 125 Khz

□ Dimensions: 76mm X 56mm X 10mm

□ Weight: 19 G



Scan product

Ref: KT104008001CPBS

Checkpoints for Guard Tour System Black Small 125Khz

Model No: 70A

□ Frequency: 125 Khz

□ Weight: 19 G



Scan product



Ref: KT104008001GTHL

Guard Tag for Guard Tour System 125Khz

Model No: 226

□ Frequency: 125 Khz

□ Dimensions: 36mm X 25mm X 6mm

□ Weight: 3.8g



Scan product

Ref: KT104008001WV4S

Guard Tour Reader WM 5000V4s With Torch

Physical: Metal Body With Rubber
Shell Outside

- Frequency: 125 khz
- Humidity: 10 % to 90 % Non-Condensing
- Battery: 3.7 V Rechargeable Battery 1150 Maa
- Card Detection: Auto Induction Card Reading
- Communication: Pogo Pin Connection Cable
- Dimensions: 148 mm X 47 mm X 30 mm
- Weight: 243 G
- Memory: 4mb Flash Rom
- Battery Life: 6000 Pieces Records
- Reading Distance: 3cm...



Scan product



Ref: KT104008001GTFV

Guard Patrolling System Real Time Full Version



Checkpoint - QR Generation
Proxy Proof Check via Photo
RFID Tag (NFC Based Mobile Device Needed)
Order of Duty
Fixed Guard Duty
Duty Performed and Duty Missed Reports
Download Logs (Excel)
Notifications
Analytical Reports
Data Retention-1 year
GPS Location of Scan
Incident Management (Text + Image + Audio)-
Guard Safety Check-
Checklist Integration- Chargeable
Works Offline



Scan product

Ref: KT104008001GTSM

Guard Tour System

Guard Tour System
Including 1 Readers, 1 Guard Tags & 10 Checkpoints



Scan product



Ref: KT104008001CHCB

JWM Guard Tour System Charging Cable

Charging Cable for JWM Guard Tour System

*Color of cable subject to change without prior notice.



×



Scan product

Ref: KT104008001CHRB

Replacement Battery For Guard Tour System

Replacement Battery for Guard Tour System



Scan product



Ref: KT104008001WMX1

Guard Tour Reader with Fingerprint WM5000X1

Dimension:- 160mm × 50mm × 34mm

Weight:- 314g

Ip Rating:- Ip67

Reading Mode:- Rfid 125 Khz

Reading Distance:- 3cm - 5cm

Communication:- Pogo Pin Usb(Drive-free), 15000 Record Uploading/min

Operating Temperature:- -40°C~+85°C

Battery:- 3.7v/2000mah Rechargeable Lithium Batteries

Batter Life

1. Read 500 Record a Day, Turn on the Flashlight for 2 Hours, for 9 Days Using.

2. Read 50...



Watch video



Scan product

Ref: KT104008001GP10

Guard Tour Reader with Fingerprint GP Finger 101

Storage Capacity: 60, 000 pieces

Alarm Clock: 200 groups

Fingerprint Record: 200 groups

Battery: 3.7V lithium rechargeable battery

Bluetooth Card: Less than 10 meters.

Communication: USB 2.0, no need to drive

Operating Temperature : -40 to + 85 Degree C

Features :

Voice prompt

Biometric Fingerprint

Impact detect

Pedometer

Flashlight

200 groups of alarm clock

Magnetic connecti...



Scan product



Ref: KT104008001GTBV

Guard Tour, Patrolling System Real Time BASE Version

Checkpoint - QR Generation
Proxy Proof Check via Photo
RFID Tag (NFC Based Mobile Device Needed)
Order of Duty
Fixed Guard Duty
Duty Performed and Duty Missed Reports
Download Logs (Excel)
Notifications
Analytical Reports
Data Retention-3 Months
Works Offline



[Watch video](#)



Scan product

Ref: KT104008001V1CH

Guard Tour System Version 1 Charger

Guard Tour Charger For Version 1



Scan product



Ref: KT104008001CHRH

Replacement Head For Guard Tour System

Replacement Head for Guard Tour System



Scan product

Ref: KT104008001CHRM

Replacement Mother Board For Guard Tour System

Replacement Mother Board for Guard Tour System



Scan product



Ref: KT104008001PT10

Guard Tour Reader with Fingerprint PT 100



Fingerprint Capacity-500
Card Capacity-1,000
Log Capacity-30,000
Sensor Fingerprint Sensor-Infrared Auto-sleep Optical Sensor
Fingerprint Algorithm ver 10
Communication Communication USB Client
Built-in RF Card Reader-125KHz Proximity Card
Power & Environment Power Supply-5V, 800mA
Battery-2,000 mA Lithium Battery
Operating Temperature-10°C~40°C
Dimension (LxWxD)-162x52x46mm
Ne...



Scan product

Ref: KT104008001WMP5

Guard Tour Reader WM5000P5, GPS Based



Model:- Wm-5000p5+
Dimension:- 150mm×78mm×18.5mm
Weight:- 260g
Color:- Yellow
Ip Rating:- Ip67
Operating Temperature:- -40°C~+85°C
Reading Mode:- Gps Location and Rfid Tag Reading
Gps Locating Accuracy:- ≤10m
Rfid Tag:- 125khz
3cm-5cm Reading Distance
Communication:- Usb(Drive-free), 8000 Record
Uploading/min
Gprs/gsm
Battery Rated Voltage:- 3.7v
Rated Capacity:- 2000amh
Dimensio...



Scan product