



N-UltraFace Strong Light

Multi-Bio Time Attendance and Access Control System

Storage Capacity

Face Capacity	3000
Finger Capacity	10,000
Card Capacity	3000
Max User	3000
Log Capacity	2,00,000

Features

World-class Face Identification Technology
High-Speed and Accurate Fingerprint Identification
Face, Fingerprint, Card authentication
2 output relay for door open.
Self-Service Inquiry



N-UltraFace

“N-UltraFace accepts face under Strong Light and Zero Light”

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

N-UltraFace accepts face under Strong Light and Zero Light.

Comprehensive software development kit(SDK) is available for development and integration.

N-UltraFace

Communication Interface

Communication	WIFI, TCP/IP, USB
---------------	-------------------

Biometric

Push Data	YES
4G GPRS	Optional
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
FAR	0.00001%
CPU	1 GHz
Verification time	<=1 second
RF card options	125kHz EM (Standard) / 13.56MHz Mifare (Optional)

Audio/Visual

LCD	2.8" TFT color screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Wiegand in & out	YES
Relay	YES
Support Exit Reader	Wiegand Reader, Remote, Push Button, No Touch

Power & Environment

Operating Temperature	0°C ~ 45°C
Power	12V DC / 2A
Dimension	200 x 150 x 95 mm



Auto Focus



Strong light Verification



Zero light Verification



Long Distance Verification



Accepts Color Finger

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control