



# N-Uface 602









(Optional)





GPRS





Access Control

## Multi-Bio Attendance and Access Control System

## **Storage Capacity**

. ,	
Face Capacity	3000
Finger Capacity	10,000
Card Capacity	10,000
Max User	10,000
Log Capacity	2,00,000

### **Features**

World-class Face Identification Technology

High-Speed and Accurate Fingerprint Identification

Face, Fingerprint, Card, Passward authentication

1 output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Not necessary of bright lights during scans.

supremely low Electric energy consumption.

Comprehensive SDK is available for development & integration.



# N-Uface 602

### Communication Interface

Communication	WIFI, TCP/IP, RS232/485, USB
---------------	------------------------------

#### Biometric

Push Data	YES
4G GPRS	Optional
GPS	Optional
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
Processor	1 GHz High Speed CPU
OS	Linux
Verification time	<=1 second
RF card options	125kHz EM (Standard) /
	13.56MHz Mifare (Optional)



LCD	4.3" touch screen 480x272 pixel
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

## Access control

Wiegand in & out	YES
Relay	YES
Support	RS485 Reader, Wiegand Reader,
	Remote, Push Button, No Touch

## Power & Environment

Battery	Yes (Optional)
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension (L*H*W)	195 x 150 x 100 mm





low light Verification



Long Distance Verification



Accepts Color Finger

Software Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

(f) BiomaxOfficial



Connect with us on

BioMax Security



