

# Frequently Asked Questions: On Cluster.

## 1. Height of Installation:

- (A) Min. Height 8 Ft. (without a mod, Fish eye)
- (B) Max Height 20 Ft. (without a mod, Fish eye)
- (C) Min. Height 8 Ft. (with a mod, Fish eye)
- (D) Max. Height 15 Ft. (with a mod, Fish eye)

## 2. Detection Width Refer (A), (B), (C), (D) from point 1.:

- Field of view: (A) =  $8 * (.5) = 4$  ft.
- Field of view: (B) =  $20 * (.5) = 10$  ft.
- Field of view: (C) =  $8 * (.75) = 6$  ft.
- Field of view: (D) =  $15 * (.75) = 12$  ft.

## 3. Power:

- Direct: Yes
- POE: No

## 4. Data Transfer:

- HTTPS: Yes
- Can be sent to onsite computer: Yes (we can provide data on a custom link if pre-informed on it).

## 5. Accuracy:

- Overall: Above 90 percent.
- During joint entries: Around 80-85 percent.

**UNYDE Systems Pvt. Ltd.**

Address : B-37, Sector- 67, Noida 201301, UP

Phone : +91(120)2484175- Email : [contact@unyde.in](mailto:contact@unyde.in)

CIN : U72900UP2017PTC093504