

GP-777HXL

HYUNDAI

Main Functions

- ENC (Environment Noise Cancelling)
- Scan
- CTCSS/DCS
- English voice prompt
- Battery Saving function
- Low battery alert
- Wide/ Narrow band selectable
- VOX
- Programming protect
- Busy Channel lock
- Squelch level selectable
- Scrambler
- TOT
- Frequency copy



General

Transmitter

Receiver

Frequency Range	Licence Free	Moduation Type	16KF43E	Sensitivity	≤ 0.2μV
Channel Capacity	16/32 channels	Spurious Radiation	≤ 7.5μW	Occupied bandwidth	≤ 16KHz
Operating Voltage	7.4VDC	Modulated noise	< -40dB	Selectivity	≥ 65dB
Operating Temperature	-20°C~+60°C	Modulation distortion	< 5%	Intermediation	≥ 55dB
Antenna	High gain antenna	Frequency stability	5ppm	Audio Output	> 1W
Antenna Impedance	50Ω	Max Fr. Deviation	≤ ±5KHz	Audio Distortion	≤ 5%
Mode of operation	Simplex	Audio response(300-3000Hz)	+6.5~-14dB	Frequency Stability	5ppm
Battery	4800(Li-ion battery)	Adjacent CH. Power	≥ 65dB	current	55mA(when standby); 150mA(when working)
		Intermediation sensitivity	8~12mv	Audio response(300-3000Hz)	+7~-12.5dB

Standard Accessories



Battery Pack



Charger



Antenna



Belt Clip



Strap Wire

