

www.tokimoinc.com





## Main Functions

			Gen	eral		
Model name				RIO(Advance) .		
Туре				Handheld two way radio		
Memory channel				16 CH		
Channel spacing				25kHz/12.5KHz		
Operating Voltage				DC7.5V		
Frequency Range				PMR 446 MHz		
Standard battery				3350mAh Li-ion Battery		
Antenna impedance				50Ω		
Operating temperature				-20℃ ~ +60℃		
Storage temperature				-40℃ ~ +80℃		
weight				300g		
Size: HxWxD (mm)				120x60x36 (not including antenna)		
Frequency modulation method				FM		
		F	tece	eiver		
Frequency stability		+/-2.5ppm	R	ated Audio 1500mW		
Reference Sensitivity	Better than-121dBm		200	Receiver SNR		≥45dB
			(1975)	audio distortion		≤5%
adjacent channel selectivity	≥ <u>65dB</u>		Channel Inhibition		≥-8 dB	
		+2dB & ≥-10dB	adjacent channel selectivity		≥50 dB	
		Tra	ans	mitter		
TX Power		0.5W	frequency stability			+/-2.5ppm
Transmitter SNR		≥40dB		maximum frequency deviation		≤5KHz
Radiated Emission		≤7.5uW	modulation characteris		153.7	+1dB ~ -3dB
adjacent channel power		≤ <u>-65dB</u>		modulation distortion		≤5%

- Waterproof IP66
- DSP Digital encryption
- Compandor
- Scrambling
- · Wide and narrow band switching
- · VOX voice control function
- Scanning function
- Squelch level setting
- · Support voice broadcast
- Battery saving function
- Analog Sub-Audio(QT)/Digital Sub-Audio(DQT)
- · Busy channel lock
- · Working mode: channel/frequency/channel+frequency
- Transmission time limit
- · Remote emergency alarm
- · Write frequency software encryption



## Standard Accessories













Antenna

**Battery Pack** 

Charger

Adapter

Belt Clip

Strap Wire





