

Professional FM Transceiver
Non-standard
CTCSS/DCS input
CTCSS/DCS encoding
and decoding

- > Scrambler
- ➤ Scan function
- ➤ Vox function
- ➤ Voice prompt
- ➤ Busy channel lock
- ➤ Battery saving function
- ➤ Compander function
- ➤ 3200 mAh Battery
- Rugged design



MAIN FUNCTIONS

Scranbler

Scan Function

VOX Function

Voice Prompt

Busy channel lock

Battery saving function

Compander function

CTCSS/DCS encoding and decoding

PC programmable

Non-standard CTCSS/DCS input

3200 mAh Battery

Rugged design

STANDARD ACCESSORIES



OPTIONAL ACCESSORIES



GENERAL

Frequency Range PMR446 Channel Capacity 16 Chanels Channel Spacing 12.5KHz/25KHz Frequency Stability ±2.5ppm Operating Temperature -20-+60°C Antenna Impedance 50 Operating Voltage 7.2V **Dimensions** 111.2x55.8x34.6mm Weight 220a Battery 3200mAh

TRANSMITTER

RF Output Power 0.5W Modulation Type 16K F3E Modulation Limiting 5KHz Modulation Character +3dB/-3dB Spurious Radiation 0.75W Adjacent Ch power >65dB Max Fr. Deviation <5KHz Occupied Bandwidth ≤16KHz

RECEIVER

Receiving Sensitivity

Adjacent Ch. Selectivity

60dB

Inter-modulation

60dB

Co-channel Suppression

-8dB

Audio Response

+2dB-10dB

Audio Output

Imw

Audio Distrotion

<3%

WWW.TOKIMOINC.COM