



**ATEX 1st Party Certified**  
CE II 3 D  
Ex tc IIIC T200°C Dc IP6X



**IECEx 3rd Party Certified**

Ex h tc IIIC T200°C (T85°C for BLSD version) Dc IP6X  
**IECEx LCIE 15.0048**

**ESD Safe** Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



## Characteristics



Static Dissipating



HEPA - Included



High Filtration Efficiency Unit



Stainless Steel General



SD Accessories - Included



Wet and Dry Recovery

- Longer life brushless motor available. Always with 4 x H14 HEPA filters
- Ideal for housekeeping and general cleaning
- By-pass Ametek® long life motor
- Includes 4 HEPA filters. Class H14. Individually factory tested
- Includes an indicator light to warn of vacuum blockage
- For wet & dry recovery
- All stainless steel SAE 304 construction (except cart)
- Stainless steel cart available
- Equipped with a heavy duty powder coated tilting cart and stainless steel drain valve for easy emptying of recovered materials
- Includes a complete static dissipative tool kit

## Specifications

C-25 EX TC WET & DRY	111778B	111778B-BLSD
<b>Model Name</b>	C-25 EX TC WET & DRY	C-25 EX TC WET & DRY BLSD
<b>Type (Powerhead)</b>	Electric	Electric
<b>Voltage</b>	220-240 V	220-240 V
<b>Hertz</b>	50/60 Hz	50/60 Hz
<b>Phase</b>	Single	Single
<b>Wattage</b>	1200 W	1100 W
<b>Power</b>	1.2 kW	1.1 kW
<b>Amperage</b>	5 A	8 A
<b>Air Flow</b>	194 m <sup>3</sup> /h	215 m <sup>3</sup> /h
<b>Vacuum Pressure</b>	2504 mm H <sub>2</sub> O	2250 mm H <sub>2</sub> O
<b>Sound Level</b>	72 dB(A)	72 dB(A)
<b>Plug Type</b>	Not Included	Not Included
<b>Suction Inlet</b>	38 mm	38 mm
<b>Cart Type</b>	Tilt Cart (TC)	Tilt Cart (TC)
<b>Dry Recovery - Tank</b>	56.8 L	56.8 L
<b>Liquid Recovery Capacity</b>	64.4 L	64.4 L
<b>Length</b>	76 cm	76 cm
<b>Width</b>	69 cm	69 cm
<b>Height</b>	124 cm	124 cm
<b>Weight (Vacuum Only)</b>	49 kg.	49 kg.
<b>Cord Length</b>	10 m	10.6 m
<b>HEPA/ULPA Filter Surface Size</b>	20 253 cm <sup>2</sup>	20 253 cm <sup>2</sup>
<b>Main Cloth Filter Surface Size</b>	3 480 cm <sup>2</sup>	3 480 cm <sup>2</sup>

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



Cable Holder Hook included on the side of the powerhead