

## DOOR FRAME METAL DETECTOR<sup>®</sup> 700318G

### Characteristics & Functions:

- Stable performance, 18 Zones.
- Based on Auto-set microcontroller.
- Detects all types of ferrous and non-ferrous
- Security level up to 100 levels.
- Sensitivity of each zone from 0 to 200.
- Self-calibration starts once powered ON.
- 2 Light bars with human body localization
- Counter: Record the pass and alarm numbers.
- Operational frequency 0-99 can be adjusted automatically.
- Waterproof mica pasted on panel & provided ABS plastic boot top bottom(IP 65 Protected).
- Harmless to the human body (Heart Pacemaker, Pregnant Women, Magnetic Floppy, Recording Tape etc.).

### Technical Parameter:

- External: approx. 2200mm (h) x 860mm (w) X 470mm (d)  $\pm 5\%$ .
- Passage: approx. 2040(h) X 720(w) X 370(d)  $\pm 5\%$ .
- Net wt.: Around 50 kgs.
- Voltage: AC100 - 240V / Frequency: 50 – 60Hz
- Power: 12W / Input: - +12V / 4.2A
- Humidity: 95% Non-condensing.
- Workplace Environment: - 20°C to 55°C.
- NABL tested
- Battery backup optional
- Ramp over optional
- Specialized counter optional
- Computer system optional



*\*Specifications are subject to change due to improvements in design.\**