



Key Features

Built-in Printer (optional)

Built-in GPS

36,000 tests records stored in memory

3.2" Touch Screen

Mouthpiece can be automatically ejected

LED light indicate where to insert mouthpiece

USB PC connection

Specification	
Sensor	Fuel Cell
Working Temperature	-10°C to 50°C
Storage Temperature	-25°C to 70°C
Size	19.5cm x 7.9cm x 3.5cm
Weight	433g included battery
Battery	7.4V 1,800mAh NI-MH rechargeable battery
Battery Life	Over 1,500 tests (over 150 tests with printouts)
Memory	16,000 tests records including all information (extendable to 32,000 records)
Display	3.2" TFT colour touch screen (65,000 colours)
Sampling System	Automatically or manually take a deep lung sample
Optional Power	Supply 12 volt car adapter or AC 6 volt adapter
Clock	Real Time Clock
Units of Measure	BrAC: mg/L, or any other units Bac: grm%, mg/ml, mg/100ml, or any other units
Detection Range	0.00% BAC to 0.40% BAC
Accuracy	0-0.10% BAC: +/-5% 0.10-0.15% BAC: +/-8% >0.15%: +/-10%
GPS	+/-5M
Printer	Thermal Printer
Connection	USB
Accessory	

Mouthpiece

Each mouthpiece is individually packed. 5 mouthpieces will be included for each device.

Sampling Cup

Each sampling cup is individually packed. 1 sampling cup will be included for each device.