

3 AAA (included)

XPP-5450G

INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

NIGHTSTICK[®]
Life Depends on Light[™]



Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



Single Body Switch. High-brightness Spotlight, Low-brightness Spotlight



ANSI IP-67 Dustproof / Waterproof with a 2 meter drop rating.



Adjustable ratchet tilt head made from an engineered polymer housing



90 LUMENS

1-800-233-2155 • 1-469-326-9400 • nightstick.com

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

3 AAA INCLUDED

ITEM NUMBER/UPC

- XPP-5450G, UPC 0 1739880300 7

MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

CERTIFICATIONS

- cETLus, CE, ATEX, IECEx, INMETRO

CASE MATERIAL

- Engineered Polymer

SPOTLIGHT LUMENS/RUNTIME

- HIGH: 90L, 13.5 hrs. runtime
- LOW: 50L, 22.75 hrs. runtime

CANDELA

- HIGH: 1,615
- LOW: 1,076

BEAM DISTANCE

- HIGH: 80m
- LOW: 65m

DUST/WATER RATING

ANSI IP-67 Dustproof / Waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 2.4 in (61 mm)
- WIDTH: 1.9 in (48 mm)
- DEPTH: 1.8 in (46 mm)
- WEIGHT: 3.5 oz (1.6 Kg)

BATTERY







- 3 AAA (Included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Headlamp
- 3 AAA batteries
- Elastic non-slip headband
- Rubber hardhat strap
- Instruction manual

FL 1 STANDARD	HIGH	LOW
	90 LUMENS	50 LUMENS
	13h	22h
	80m	65m
	1615cd	1076cd
	2m	
	1m	

Bayco Products, Inc. XPP-5450G
640 S. Sanden Blvd., Wylie, TX 75098



Intertek

ID 4003544
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CE 2575



SEE INSTRUCTION MANUAL
VOIR MANUEL

MFG MM-YY

CLASS I DIV 1 GRPS A-D T4
CLASS II & III GRPS E-G T135C
CLASS I ZONE 0 AEx ia IIC T4 Ga
CLASS I ZONE 0 Ex ia IIC T4 Ga
Ⓢ II 1 G Ex ia op is IIC T4 Ga
Ex ia op is IIC T4 Ga
Intertek ITS 13 ATEX27854X
IECEx ETL 17.0002X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell AAA Alkaline

CERTIFIED

