



PESO



TECHNICAL DATA: Model : FCG7301

DESCRIPTION:

INTRINSIC SAFETY (Ex-ia) SUITABLE FOR USE IN GAS GROUP I, IIA, IIB, IIC AREA AS PER IS/IEC 60079-11:2011

MARKING: Ex ia IIC T4 G6
Ex tb IIIC T85°C Db

PROTECTION: IP68

AREA CLASSIFICATION: ZONE - 1 & 2

CERTIFICATION: CIMFR/BIS/PESO

SPECIAL INSTRUCTION:

1. REFER OPERATING INSTRUCTION MANUAL BEFORE USE.
2. THE BATTERY CHARGING SHOULD BE DONE IN SAFE AREA ONLY



Ex-d Torch

KEY FEATURES:

- Explosion proof
- Intrinsically safe LED Hand Torch/flash light for use in zone 1 & 2 hazardous areas
- Ip68
- High powered OSRAM LED
- Charging time : 6hrs
- Running time: High : 9hrs, Low:18hrs
- Battery : 2.2Ah Lithium-ion
- Up to 200m beam
- Dimesions :Ø56 x 185L ± 5mm

Typical application include Gas station, manufacturing plants, chemical and petrochemical processing facilities, Sewage treatment plants, off-shore and dockside installation

